

EQQ LiteRex halogen free installation cable

5G1,5



For Fixed installations indoors and outdoors. Not to be laid in soil nor directly in cast concrete. UV-protected outer sheath and core insulation.

Special property	Halogen free EN 60754, minimal smoke production EN 61034
Fire class	Dca-s2, d2, a2
CPR - DoP	2018010_DOP.pdf
Conductor	Circular solid copper, EN 60228 class 1
Insulation	Halogen free UV-resistnat polyethylene
Identification	3 core: yellow/green, blue, brown 4 core: yellow/green, blue, brown, black 5 core yellow/green, blue, brown, black, grey
Outer sheath	Halogen free UV-resistant polyolefin compound, colour white

Size: 5G1,5
Reka code: 1254732--en
Packing (m): 100 coil

Voltage	300/500 V
Diameter (mm)	10
Weight kg/km	140

Minimum allowed bending radius in installation (cm)	9
Minimum allowed bending radius in final installation (cm)	3
Maximum allowed pulling force when pulling from conductors (kN)	0,38
Maximum DC resistance of phase conductor, +20°C (ohm/km)	12,1
Minimum handling temperature (°C)	-15
Maximum conductor temperature (°C)	70
Conductor short-circuit temperature, 5 s (°C)	160
Product number	1254732
GTIN code	6438176224151



Saved from www.rekacables.com website 20.1.2021. Please note that product details can change.