

ENSTO

Porcelain stay insulator

SDI4.5

Code SDI4.5
GTIN 6418677418556
Name Porcelain stay insulator
24 kV

Description Porcelain stay insulator is suitable for installation in stay wires up to 52 mm².
Conforms with standard SFS 3741.
Creepage distance is 95 mm.

Vendor Ensto Finland Oy



Technical specification

Dimensions

Weight: 2.15 kg
Creepage distance: 95 mm

Electrical values

Highest system voltage: 24 kV
Wet power frequency withstand voltage: ≥ 24 kV

Mechanical

Max. continuous load: 35 kN
SMFL: 120 kN

Features

For conductor size: 16-52 (68)

Others

ETIM Class: EC003514

ETIM Technical specification

etim

Model: Tension insulator
Rated voltage: 0.024 kV

Material:	Porcelain
Length:	175 mm
Diameter:	100 mm
Weight:	2.15 kg
Creepage path:	95 mm
Wet power frequency withstand voltage:	24 kV
Breaking load:	120 kN

Packaging

Carton (Default package)

Package size:	6 pce
Depth:	320 mm
Width:	225 mm
Height:	190 mm
Weight:	13.4 kg
Volume:	13.68 l

Pallet package

Package size:	288 pce
Depth:	1200 mm
Width:	800 mm
Weight:	663.2 kg