

ENSTO

Arc protection device

SEW20.2

Code	SEW20.2
GTIN	6438100305543
Name	Arc protection device PAS/BLL-T 50-157 mm ² AlMgSi, with plain horn and Al-thread
Description	The connector SEW20.2 includes an Al-thread to connect the connector to the neck of the insulator. The length of 25 mm ² Al thread is 2.1 m. The connector is watertight by silicone greased teeth.
Vendor	Ensto Finland Oy



Technical specification

Certificates

Standards: EN 50397-2:2009

Features

Bolt: 2xM10
 For conductor size: BLX / BLL 50-157
 Plastic cover: SP16

Mechanical

Tightening torque Nm: 40 Nm

Others

ETIM Class: EC001062

Dimensions

Length: 295 mm
 Width: 200 mm
 Height: 85 mm
 Weight: 0.6273 kg

ETIM Technical specification

etim

Nominal cross section main conductor SM:	50 ... 157 mm ²
Material main conductor:	Aluminium
Material branch conductor:	Aluminium
Terminal insulated:	No
Clamping channel opening main conductor:	Both sides open
Clamping channel opening branch conductor:	Both sides open
Surface protection:	Bare
Type of connection:	Insulation piercing connector IPC

Packaging**Plastic bag**

Package size:	3 pcs
Depth:	10 mm
Width:	260 mm
Height:	550 mm
Weight:	1.895 kg
Volume:	1.43 l

Carton (Default package)

Package size:	24 pcs
Depth:	400 mm
Width:	295 mm
Height:	240 mm
Weight:	15.661 kg
Volume:	28.32 l

Pallet package

Package size:	768 pcs
Depth:	1200 mm
Width:	800 mm
Height:	1130 mm
Weight:	521.146 kg
Volume:	1084.8 l