

ENSTO

Glass tension insulator string

SH193

Code	SH193
GTIN	6418677407062
Name	Glass tension insulator string 24 kV, 40 kN, ball eye and socket tongue
Description	Glass tension insulator string can be used either as a suspension set equipped with suitable clamp or as a tension set equipped with suitable tension clamp. Number of insulators 2.
Vendor	Ensto Finland Oy



Technical specification

Dimensions

Weight:	3.619 kg
Creepage distance:	380 mm
Total length:	345 mm

Electrical values

Highest system voltage:	24 kV
-------------------------	-------

Features

End fittings:	ball / socket
Number of insulators:	2

Mechanical

Breaking load:	40 kN
Highest permitted load in use:	16 kN

Others

ETIM Class:	EC003514
-------------	----------

ETIM Technical specification

etim

Model:	Tension insulator
Rated voltage:	24 kV
Material:	Glass
Length:	345 mm
Diameter:	175 mm
Weight:	4.4 kg
Creepage path:	380 mm
Breaking load:	40000 kN

Packaging

Carton (Default package)

Package size:	1 pce
Depth:	320 mm
Width:	200 mm
Height:	200 mm
Weight:	4.119 kg
Volume:	12.8 l

Pallet package

Package size:	60 pce
Depth:	1200 mm
Width:	800 mm
Height:	1150 mm
Weight:	267.14 kg
Volume:	1104 l