



VS218PZF

**Small distributor,golf,surface,MM,2row,36M,white door,slotted**

## Technical properties

### Architecture

Fixing mode	surface-mounting
-------------	------------------

### Functions

With a pipe-in lead	Yes
---------------------	-----

### Configuration

Number of modules	36
-------------------	----

### Electric current

Rated current	63 A
---------------	------

### Dimensions

Depth of wall niche	72 mm
Depth of installed product	99 mm
Internal depth	99 mm
Height of installed product	377 mm
Width of installed product	390 mm

### Cover, door

Type of door closing	Latch
Identification od protection index	40
Interlockable	No
Number of keylock of the door	0
Cover type	With Notch
Door locking	without
Door leave	single
Cover type	Door
Transparent cover or door	No

### Materials

Colour	pure white
Colour	white
RAL colour	RAL 9010 - Pure white
Material	plastic
Type of surface treatment	untreated

### Installation, mounting

Suitable for outdoor use	No
--------------------------	----

### Settings

Subject to technical modifications

Enclosure type	Distributor empty cabinet
----------------	---------------------------

#### Equipment

Number of units	18
Number of rows	2
Quantity of rails	2
Can be accessorized	Yes
Number of openings for flange plates	0
Extension possible	Yes
Earthing terminal block	No
Neutral terminal block	No
Signal passing door	Yes

#### Standards

GWT Glow wire test	650 °C
European directive WEEE	concerned

#### Safety

IK protection code against mechanical impacts	IK07
Protection class	isol.class II