
PRODUCT-DETAILS

4332.0193.0

KSNS 440 Neutral busbar



General Information

Global Commercial Alias	4332.0193.0
Extended Product Type	KSNS 440
Product ID	2CGX043320193
EAN	7331980004959
Catalog Description	KSNS 440 Neutral busbar
Long Description	Busbars without protection against accidental contact (type PEN and N), IP 00

Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CGC0049
RoHS Information	2CGC0038

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85369010
Country of Origin	Sweden (SE)

Popular Downloads

Data Sheet, Technical Information	2CGC0036
Instructions and Manuals	No Instructions and Manuals needed

Dimensions

Product Net Width	585 mm
Product Net Height	30 mm
Product Net Depth / Length	20 mm
Product Net Weight	0.35 kg

Technical

Conventional Thermal Current (I_{the})	400 A
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	690 V
Rated Peak Withstand Current Low Voltage (I_{pk})	55 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 0.2 s 30 kiloampere rms
Rated Conditional Short-Circuit Current (I_{nc})	(3//315 A fuse, 690 V) 50 kiloampere rms (3//250 A fuse, 690 V) 85 kiloampere rms
Degree of Protection	acc. to IEC 60529 IP00

Certificates and Declarations

Declaration of Conformity - CE	2CGC0020
REACH Declaration	2CGC0049

Container Information

Package Level 1 Units	1 euro pallet
Package Level 1 Width	30 mm
Package Level 1 Depth / Length	585 mm
Package Level 1 Height	20 mm
Package Level 1 Gross Weight	0.35 kg
Package Level 1 EAN	7331980004959

Classifications

ETIM 7	EC001522 - Busbar
ETIM 8	EC001522 - Busbar

ETIM 9	EC001522 - Busbar
eClass	V11.1 : 27370303
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
E-Number (Finland)	5451706
E-Number (Sweden)	0732891

Categories

Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → Kabeldon IP-System

