

ENSTO

Cold shrink outdoor term

COTW1.2403L

Tip COTW1.2403L
 GTIN 6438100304331
 Nume Cold shrink outdoor term
 12.7/22 (24) kV 70-240 mm² 3x1-core with lug

Descriere Cold shrink outdoor termination for 1-core cables with Al/Cu conductor, polymeric insulation and Al-laminate screen. The kit contains components for three cable cores. Mechanical lugs for conductor and screen wire connection are included in the kit. The termination kits include cold shrinkable termination bodies with integrated stress control elements, copper braids for screen connection and all the additional components needed for assembly.

Vânzător Ensto Finland Oy



Specificații tehnice

Features

Rated voltage U ₀ /U (U _m):	12.7/22 (24) kV
Shrink technique:	Cold shrink
Accessory type:	Termination, outdoor
Conductor material:	Al/Cu
Conductor size round:	70 ... 240 mm ²
Screen/shield connection:	≤ 25 mm ²
Distanță de conturare:	550 mm
Diametru interior:	100 mm
Termination length (Lt):	400 mm

Cable

Conductor size U _m = 12 kV:	95 ... 240 mm ²
Conductor size U _m = 24 kV:	70 ... 240 mm ²
Diametrul la nivelul izolației:	18,4 ... 36 mm

Diameter outer sheath:	28 ... 44 mm
Material insulation:	polimerică
Material screen/shield:	Al-laminate
Nr. nuclee:	3
Spiral inner diam.:	50 mm

Temperatures

Installation temperature:	-25 ... 50 °C
Temperatură de operare:	50 ... 90 °C
Storage temperature:	5 ... 40 °C

Others

ETIM Class:	EC003520
-------------	----------

Dimensions

Net Weight:	3,024 kg
-------------	----------

ETIM Specificații tehnice

etim

Number of cores:	3
Suitable for indoor use:	No
Suitable for outdoor use:	Yes
Type of cable termination:	Cold-shrink
Material insulating material:	Plastic
Cable lug included:	Yes
Type of cable lug:	Screw connection
Nominal cross section:	70 ... 240 mm ²

Packaging

Carton (Default package)

Package size:	1 pcs
Depth:	383 mm
Width:	258 mm
Height:	131 mm
Weight:	3,24 kg
Volume:	12,944634 l

Pallet package

Package size:	63 pce
Depth:	1200 mm
Width:	800 mm
Height:	1140 mm
Weight:	224,12 kg
Volume:	1094,4 l

