

Stainless Steel Cable Ties

Cable Ties

Tork Stainless steel cable ties are made of 304 and 316 quality stainless steel material. The ball system used in the lock design helps the product to be applied both easily and quickly. Tork Stainless cable ties, which are resistant to high temperature, corrosion and flame, are also extremely resistant to UV rays and ideal in all outdoor areas where photovoltaic and solar energy are used. The use of AISI 316 stainless is recommended for aggressive areas that require very high corrosion resistance.

- The cable ties can be used manually or with a special tool.
- The ball lock system ensures less effort and time savings.
- They can be used as a fire security due to their superior strength.
- Damage to the electrical insulation of the cable is prevented thanks to its smooth edge structure.

Technical Specifications

- Raw material: AISI 304 or 316 stainless steel
- Halogen free: Yes
- Working temperature: -80 ° C + 538 ° C
- Fireproof Material: Yes
- Where it is resistant: Excellent resistance to acids, oils, greases, chemicals, sea water and UV rays.

Application Areas

- In electrical installations and fire installations (used as flame security to fix equipment that needs to be protected in case of fire)
- In the shipbuilding industry, petrochemical plants, oil platforms and fire risk environments
- Can be used in photovoltaic plants where high mechanical and UV resistance is required



Box content

| Product Code | Size | | Colour | Tighten Range | Max Tensile Strength | Quantity In a Nylon Bag | Quantity In a Carton Box |
|----------------|--------------|-------------|--------|---------------|----------------------|-------------------------|--------------------------|
| | Length (L) | Width (B) | | | | | |
| | mm | mm | | max Ø mm | Kg / f | | |
| TRK-150-46-W4 | 150 | 4.6 | METAL | 33 | 55 | 100 | 8000 |
| TRK-200-46-W4 | 200 | 4.6 | METAL | 50 | 55 | 100 | 6000 |
| TRK-250-46-W4 | 250 | 4.6 | METAL | 67 | 55 | 100 | 5000 |
| TRK-300-46-W4 | 300 | 4.6 | METAL | 75 | 55 | 100 | 5000 |
| TRK-370-46-W4 | 370 | 4.6 | METAL | 102 | 55 | 100 | 4000 |
| TRK-450-46-W4 | 450 | 4.6 | METAL | 130 | 55 | 100 | 3000 |
| TRK-520-46-W4 | 520 | 4.6 | METAL | 152 | 55 | 100 | 3000 |
| TRK-680-46-W4 | 680 | 4.6 | METAL | 203 | 55 | 100 | 2000 |
| TRK-840-46-W4 | 840 | 4.6 | METAL | 250 | 55 | 100 | 1000 |
| TRK-200-79-W4 | 200 | 7.9 | METAL | 50 | 120 | 100 | 5000 |
| TRK-300-79-W4 | 300 | 7.9 | METAL | 75 | 120 | 100 | 4000 |
| TRK-370-79-W4 | 370 | 7.9 | METAL | 102 | 120 | 100 | 3000 |
| TRK-450-79-W4 | 450 | 7.9 | METAL | 130 | 120 | 100 | 2000 |
| TRK-520-79-W4 | 520 | 7.9 | METAL | 152 | 120 | 100 | 2000 |
| TRK-680-79-W4 | 680 | 7.9 | METAL | 203 | 120 | 100 | 2000 |
| TRK-840-79-W4 | 840 | 7.9 | METAL | 250 | 120 | 100 | 1000 |
| TRK-1000-79-W4 | 1000 | 7.9 | METAL | 300 | 120 | 100 | 1000 |