

# Airam Led

## 7.2W 15000h BX

For all residential lighting needs

A very comprehensive lamp series that provides a solution for all residential lighting needs. These lightweight, durable lamps can fully replace incandescent bulbs, halogen lamps and compact fluorescent lamps. The lamps have a pleasant, warm white (2700 K) colour temperature. The opal light source provides non-glaring light. The eco-friendly cardboard packages are colour-coded. The colour indicates the corresponding incandescent bulb, making the choice simpler for the consumer. Technical specifications are also clearly presented. Ensure the compatibility of the range's 12V lamps with your transformer.

Opal P45 bulb LED lamp 7.2W 2700K E27 806lm  
15000h 45x84mm, cardboard packing. Supply  
frequency ~50/60Hz.



7.2W 15000h BX			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4713775	A7GAEE	0.03	Airam Led

## 7.2W 15000h BX

EC001959

Mounting	
Degree of protection (IP)	Other

  

Structure	
Colour	White
Housing colour	White

  

Dimming and control	
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	Yes
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

  

Photometric data	
Luminous flux (min) (lm)	806
Luminous flux (max) (lm)	806
Colour rendering index CRI	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	2700
Colour temperature (max) (K)	2700
Beam angle (min)	240
Beam angle (max)	240
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG0

  

Lifetime and capacity	
-----------------------	--

  

Measurements	
Diameter (mm)	45
Length (mm)	84

  

Electrotechnical data	
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	60
Nominal current (max) (mA)	60
Power factor	0.5
Voltage type	AC
Energy Efficiency Index (EEI)	0.112