Airam Led 7.2W 15000h BX

For all residential lighting needs

A very comprehensive lamp series that provides a solution for all residential lighting needs. These lightweight, durable lamps can fully replace incandescent bulbs, halogen lamps and compact fluorescent lamps. The lamps have a pleasant, warm white (2700 K) colour temperature. The opal light source provides non-glaring light. The eco-friendly cardboard packages are colour-coded. The colour indicates the corresponding incandescent bulb, making the choice simpler for the consumer. Technical specifications are also clearly presented. Ensure the compatibility of the range's 12V lamps with your transformer.

Opal P45 bulb LED lamp 7.2W 2700K E14 806lm 15000h 45x85mm, cardboard packing. Supply frequency $\sim 50/60$ Hz.

7.2W 15000h BX			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4713774	A7GAED	0.04	Airam Led



7.2W 15000h BX

EC001959

M ii	
Mounting	0.1
Degree of protection (IP)	Other
Structure	
Colour	White
Housing colour	White
Discoving and control	
Dimming and control	N1
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	Yes
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Photometric data	00/
Luminous flux (min) (lm)	806
Luminous flux (max) (lm)	806
Colour rendering index CRI	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	2700
Colour temperature (max) (K)	2700
Beam angle (min)	240
Beam angle (max)	240
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG0
Lifetime and capacity	
спенте ана сарасну	
Measurements	
Diameter (mm)	45
Length (mm)	85
Electrotechnical data	
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	60
Nominal current (max) (mA)	60
Power factor	0.5
Voltage type	AC
Energy Efficiency Index (EEI)	0.112

