## Airam Led 4W 130cd 15000h BL

For all residential lighting needs

A very comprehensive lamp series that provides a solution for all residential lighting needs. These lightweight, durable lamps can fully replace incandescent bulbs, halogen lamps and compact fluorescent lamps. The lamps have a pleasant, warm white (2700 K) colour temperature. The opal light source provides non-glaring light. The eco-friendly cardboard packages are colour-coded. The colour indicates the corresponding incandescent bulb, making the choice simpler for the consumer. Technical specifications are also clearly presented. Ensure the compatibility of the range's 12V lamps with your transformer.

Opal R50 reflector LED lamp 4W 2700K E14 450lm 130cd 110D 15000h 50x85mm, blister packing. Supply frequency  $\sim 50/60$ Hz.

4W 130cd 15000h	BL		
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4711366	A7UACK	0.035	Airam Led



## 4W 130cd 15000h BL

EC001959

Mounting	
mounting	
Degree of protection (IP)	Other
Structure	
Colour	White
Housing colour	White
,	
Dimming and control	
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	Yes
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Sapport available	
Photometric data	
Luminous flux (min) (lm)	450
Luminous flux (max) (lm)	450
Luminous intensity (cd)	130
Colour rendering index CRI	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	2700
Colour temperature (max) (K)	2700
Beam angle (min)	110
Beam angle (max)	110
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1
Thotoblotogical safety according to 214 02471	1101
Lifetime and capacity	
Energine and capacity	
Massuraments	
Measurements Diameter (mm)	50
Diameter (mm)	50
	50 85
Diameter (mm) Length (mm)	
Diameter (mm) Length (mm) Electrotechnical data	85
Diameter (mm) Length (mm)  Electrotechnical data Nominal voltage (min) (V)	85 220
Diameter (mm) Length (mm)  Electrotechnical data Nominal voltage (min) (V) Nominal voltage (max) (V)	220 240
Diameter (mm)  Length (mm)  Electrotechnical data  Nominal voltage (min) (V)  Nominal voltage (max) (V)  Nominal current (min) (mA)	220 240 40
Diameter (mm)  Length (mm)  Electrotechnical data  Nominal voltage (min) (V)  Nominal voltage (max) (V)  Nominal current (min) (mA)  Nominal current (max) (mA)	220 240 40 40
Diameter (mm)  Length (mm)  Electrotechnical data  Nominal voltage (min) (V)  Nominal voltage (max) (V)  Nominal current (min) (mA)  Nominal current (max) (mA)  Power factor	220 240 40 40 0.5
Diameter (mm)  Length (mm)  Electrotechnical data  Nominal voltage (min) (V)  Nominal voltage (max) (V)  Nominal current (min) (mA)  Nominal current (max) (mA)	220 240 40 40

