

## PRODUCT DATASHEET

### HALOSTAR STARLITE 10 W 12 V G4

HALOSTAR STARLITE® 2000 | Low-voltage halogen lamps with pin base



#### Areas of application

- General illumination
- Entrance lighting
- Accent lighting
- Lighting for reading
- Garden lighting
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings
- Outdoor applications only in suitable luminaires

#### Product benefits

- Brilliant accent light
- Incredibly small dimensions for revolutionary new luminaire designs
- Approved for use in open luminaires (to IEC 60598-1)
- Axial filament for optimum directional light
- Special pins for corrosion protection
- UV filter
- Contains no mercury

#### Product features

- Average life: 2,000 h
- 100 % dimmable
- Color rendering index  $R_a$ : 100




## TECHNICAL DATA

### Electrical data

|                      |         |
|----------------------|---------|
| Nominal wattage      | 10 W    |
| Construction wattage | 10.00 W |
| Nominal voltage      | 12 V    |

### Photometrical data

|                           |            |
|---------------------------|------------|
| Luminous flux             | 130 lm     |
| Luminous efficacy         | 13 lm/W    |
| Light color (designation) | Warm White |
| Color temperature         | 2800 K     |
| Color rendering index Ra  | 100        |
| Light color               | 1028       |
| UV protection             | Yes        |



349642\_HAL\_NV\_UVS

### Light technical data

|               |       |
|---------------|-------|
| Starting time | 0.0 s |
|---------------|-------|

### Dimensions & Weight

|                           |          |
|---------------------------|----------|
| Overall length            | 33.00 mm |
| Light center length (LCL) | 22,0 mm  |
| Diameter                  | 10.00 mm |
| Product weight            | 1.17 g   |

### Lifespan

|                            |       |
|----------------------------|-------|
| Number of switching cycles | 50000 |
|----------------------------|-------|

### Additional product data

|                             |     |
|-----------------------------|-----|
| Base (standard designation) | G4  |
| Mercury-free                | Yes |

### Capabilities

|                  |     |
|------------------|-----|
| Dimmable         | Yes |
| Burning position | Any |

### Certificates & Standards

|                         |                 |
|-------------------------|-----------------|
| Energy efficiency class | G               |
| Energy consumption      | 10.00 kWh/1000h |


### Country-specific categorizations

|                 |                            |
|-----------------|----------------------------|
| ILCOS           | HSGS/C/AXUB-10-12-G4-10/22 |
| Order reference | 64415 S AX                 |


### Energy labelling regulation data acc EU 2019/2015

|   |              |
|---|--------------|
| Lighting technology used                            | OTHER        |
| Non-directional or directional                      | NDLS         |
| Mains or non-mains                                  | NMLS         |
| Light source cap-type (or other electric interface) | G4           |
| Connected light source (CLS)                        | No           |
| Color-tuneable light source                         | No           |
| Envelope  | No           |
| High luminance light source                         | No           |
| Anti-glare shield                                   | No           |
| Correlated colour temperature type                  | SINGLE_VALUE |
| Claim of equivalent power                           | No           |
| Length  | 33.00 mm     |
| Height  | 10.00 mm     |
| Width   | 10.00 mm     |
| Chromaticity coordinate x                           | 0.452        |
| Chromaticity coordinate y                           | 0.409        |
| Beam angle correspondence                           | SPHERE_360   |
| EPREL ID  | 714476       |

### DOWNLOAD DATA

| Documents and certificates   |                               | Document name               |
|--|-------------------------------|-----------------------------|
|  | Declarations Of Conformity CE | CE Declaration HAL LOW VOLT |

---

| Photometric and lighting design files   |                             | Document name     |
|---|-----------------------------|-------------------|
|  | Spectral power distribution | 349642_HAL_NV_UVS |

**LOGISTICAL DATA**

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075094178 | Folding box<br>1             | 25 mm x 23 mm x 70 mm                | 3.10 g       | 0.04 dm <sup>3</sup>  |
| 4058075103658 | Unpacked<br>1                | 25 mm x 23 mm x 70 mm                | 1.00 g       | 0.04 dm <sup>3</sup>  |
| 4058075164130 | Bundle<br>10                 | 126 mm x 47 mm x 71 mm               | 26.00 g      | 0.42 dm <sup>3</sup>  |
| 4058075164239 | Bundle<br>5                  | 115 mm x 25 mm x 70 mm               | 24.00 g      | 0.20 dm <sup>3</sup>  |
| 4058075307957 | Bundle<br>2                  | 23 mm x 50 mm x 70 mm                | 7.00 g       | 0.08 dm <sup>3</sup>  |
| 4058075094185 | Shipping box<br>40           | 144 mm x 107 mm x 121 mm             | 165.00 g     | 1.86 dm <sup>3</sup>  |
| 4058075103665 | Shipping box<br>5,000        | 410 mm x 310 mm x 435 mm             | 7875.00 g    | 55.29 dm <sup>3</sup> |
| 4058075164246 | Shipping box<br>40           | 144 mm x 107 mm x 121 mm             | 165.00 g     | 1.86 dm <sup>3</sup>  |
| 4058075307964 | Shipping box<br>16           | 192 mm x 59 mm x 80 mm               | 94.00 g      | 0.91 dm <sup>3</sup>  |
| 4058075307971 | Shipping box<br>192          | 366 mm x 201 mm x 176 mm             | 1284.00 g    | 12.95 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.