

PRODUCT DATASHEET

HQI-BT 400 W/D PRO

POWERSTAR HQI®-T | Metal halide lamps with quartz technology for enclosed luminaires



Areas of application

- Factories and workshops
- Sports halls and multi-purpose halls
- Industrial installations
- Docks and port facilities
- Marshaling yards, container transshipment facilities
- Buildings, monuments, bridges
- Approved only for use in enclosed luminaires
- Outdoor applications only in suitable luminaires

Product benefits

- E40 screw base for simple lamp handling
- UV values significantly below the maximum permitted thresholds to IEC 61167 thanks to UV filter

Product features

- POWERSTAR® quartz technology
- Light colors: neutral white (N), daylight (D)



TECHNICAL DATA


Electrical data

Nominal wattage	400 W
Construction wattage	430.00 W
Nominal voltage	115 V
Ignition voltage	4.0/5.0 kVp ¹⁾
Operating mode	Conventional control gear (CCG) and ignitor
Nominal current	4 A
PFC capacitor at 50 Hz	45 µF

1) Minimum / Maximum

Photometrical data

Luminous flux	34000 lm
Luminous efficacy	79 lm/W
Color temperature	5500 K
Color rendering index Ra	≤ 87
Light color	855
Rated LLMF at 2,000 h	0.92
Rated LLMF at 4,000 h	0.90
Rated LLMF at 6,000 h	0.87
Rated LLMF at 8,000 h	0.85
Rated LLMF at 12,000 h	0.81
UV protection	Yes



384076_HQI_T_D_PRO

Dimensions & Weight

Overall length	290.00 mm
----------------	-----------

Light center length (LCL)	175,0 mm
Diameter	62 mm
Product weight	220.00 g

Lifespan

Rated lamp survival factor at 2,000 h	0.96
Rated lamp survival factor at 4,000 h	0.94
Rated lamp survival factor at 6,000 h	0.93
Rated lamp survival factor at 8,000 h	0.88
Rated lamp survival factor at 12,000 h	0.81
Lifespan B50	16000 h

Additional product data

Base (standard designation)	E40
Mercury content	69.0 mg
Design / version	Clear
Product remark	With NAV® control gear

Capabilities

Dimmable	No
Burning position	Any
Enclosed luminaire required	Yes
Hot restart	No

Certificates & Standards

Energy efficiency class	G
Energy consumption	430.00 kWh/1000h

Country-specific categorizations





ILCOS	MT/UB-400/960-H/E/SL-E40-62/285
Order reference	HQI-BT 400W/D P


Energy labelling regulation data acc EU 2019/2015

Lighting technology used	MH
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	E40
Connected light source (CLS)	No

Color-tuneable light source	No
Envelope	SECOND
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	290.00 mm
Height	62 mm
Width	62 mm
Chromaticity coordinate x	0,332
Chromaticity coordinate y	0,349
Beam angle correspondence	SPHERE_360
EPREL ID	546563
Model number	AC34337

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction	High Intensity Discharge Lamp UI
 Declarations Of Conformity CE	EC Declaration of Conformity - 2021 9C1-4077886-EN-00 - HQI
 Certificates	EAC RU C-DE.AYA46.B.16087_20 13.10.2020-12.10.2025 Rostest-Moskva - MH single capped
 Certificates	EAC N RU D-DE.MU62.B.00932_20 06.03.2020-05.03.2025 Prommash Test - MH

Photometric and lighting design files	Document name
 Spectral power distribution	384076_HQI_T_D_PRO

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321677860	Sleeve 1	65 mm x 65 mm x 325 mm	260.00 g	1.37 dm ³
4008321677877	Shipping box 12	318 mm x 253 mm x 342 mm	3534.00 g	27.52 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.