

Eaton 40071354875

Catalog Number: 40071354875

Eaton Atlantic LED, Exit sign, 24m viewing distance, Single side, CGLine + technology, LED, Maintained / Non-Maintained operation, IP65, 1h/3h/8h selectable duration, Battery heater for low temperatures down to -20°

General specifications

Product Name	Catalog Number
Eaton Atlantic LED SC Emergency Luminaire	40071354875
	EAN
	4012539344490
Product Length/Depth	Product Height
303 mm	62 mm
Product Width	Product Weight
136 mm	1.4 kg
Certifications	
CE	

defaultTaxonomyAttributeLabel

Battery voltage

3.7 VDC

Battery quality

Lithium-ions

Glow wire test

850 °C

Protection class

I

Outdoor use compliance

True

Explosion protected

False

Degree of protection

IP65

Mode

Maintained / Non-Maintained (M / NM)

Lamp type

LED not exchangeable

With light source

True

Lamp holder

Other

Lamp power

1.6 W

Type of indicator

Only single-sided

Monitoring equipment

Safety module for monitoring (central feeded system)

Power supply system

Peripheral (individual battery)

Voltage type

AC

Power factor

.91

Resources

Catalogs

[eaton-el-cps-catalog-2020-gbr.pdf](#)

Installation instructions

[eaton-emergency-lighting-self-contained-exit-safety-atlantic-led-safety-instructions-all-lang.pdf](#)

Manuals and user guides

[eaton-emergency-lighting-self-contained-exit-safety-atlantic-manual-en.pdf](#)

[eaton-emergency-lighting-self-contained-exit-safety-atlantic-led-manual-en-de.pdf](#)

Technical data sheets

Atlantic LED CGLine+

[eaton-emergency-lighting-exit-safety-atlantic-datasheet-en-uk.pdf](#)

[eaton-emergency-lighting-self-contained-exit-safety-atlantic-led-datasheet-en.pdf](#)

Wiring system

Continuous circuit/emergency circuit

With remote switch connection

True

Reserve-polarity protected

True

Conductor cross section

2.5

Connection type

Plug-in connection

Rated life time L70/B50 at 25 °C

50000 hour

Rated life time L90/B10 at 25 °C

50000 hour

Type of control gear

LED operating device current-controlled

Type of wiring

Suitable for through wiring

Nominal voltage AC - max

240 V

Nominal voltage AC - min

220 V

Effective power at mains operation (50cd)

9.3 W

Nominal operation time - min

1 hour

Nominal operation time - max

8 hour

Autonomy

1/3/8 hours

Material housing

Aluminium

Color housing

Grey

Material cover

Plastic, transparent

Labelling type

Insert sheet/plate

Pictogram included

False

Number Of Poles (Numeric)

6

Impact strength

IK10

Kind of luminaire

Safety and exit sign luminaire

Color temperature - max

6500 K

Color temperature - min

6500 K

Light distributor

Diffuser lens/optic/panel

Energy efficiency class of the built-in lamp

A++, A+, A (LED)

Function

Escape route signage

Color of light

White

Color rendering index (CRI)

70

Luminaire With Limited Surface Temperature, Sign D

True

Number of lighting heads

1

Viewing distance

24 m

Data connection terminal

1.5 mm²

Frequency

50/60 Hz

Main connection terminal

2.5mm²

Testing system

CGLine +



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)