

# Eaton 40071354878

Catalog Number: 40071354878

Eaton Atlantic LED, Safety lighting, Open area, CGLine + technology, LED, Maintained / Non-Maintained operation, IP65, 225lm, 1h/3h/8h selectable duration, Battery heater for low temperatures down to -20°

## General specifications



Photo is representative

Product Name	Catalog Number
Eaton Atlantic LED SC Emergency Luminaire	40071354878
	EAN
	4012539344520
Product Length/Depth	Product Height
303 mm	62 mm
Product Width	Product Weight
136 mm	1.42 kg
Certifications	
CE	

## defaultTaxonomyAttributeLabel

### Battery voltage

3.7 V

### Battery quality

Lithium-ions

### Glow wire test

850 °C

### Protection class

I

### Outdoor use compliance

True

### Explosion protected

False

### Degree of protection

IP65

### Mode

Maintained / Non-Maintained (M / NM)

### Lamp type

LED not exchangeable

### With light source

True

### Lamp holder

Other

### Lamp power

1.6 W

### Monitoring equipment

Safety module for monitoring (central feeded system)

### Power supply system

Peripheral (individual battery)

### Voltage type

AC

### Power factor

.91

### Wiring system

Continuous circuit/emergency circuit

## Resources

### Catalogs

[eaton-el-cps-catalog-2020-gbr.pdf](#)

### Installation instructions

[eaton-emergency-lighting-self-contained-exit-safety-atlantic-led-safety-instructions-all-lang.pdf](#)

### Manuals and user guides

[eaton-emergency-lighting-self-contained-exit-safety-atlantic-manual-en.pdf](#)

[eaton-emergency-lighting-self-contained-exit-safety-atlantic-led-manual-en-de.pdf](#)

### Technical data sheets

[eaton-emergency-lighting-exit-safety-atlantic-datasheet-en-uk.pdf](#)

[eaton-emergency-lighting-self-contained-exit-safety-atlantic-led-datasheet-en.pdf](#)

[Atlantic LED / Outdoor Wall CGLine+](#)

With remote switch connection

True

Reserve-polarity protected

True

Conductor cross section

2.5

Connection type

Plug-in connection

Rated life time L70/B50 at 25 °C

13.88888889 hour

Rated life time L90/B10 at 25 °C

50000 hour

Type of control gear

LED operating device current-controlled

Type of wiring

Suitable for through wiring

Nominal voltage AC - max

240 V

Nominal voltage AC - min

220 V

Effective power at mains operation (50cd)

9.3 W

Nominal operation time - min

1 hour

Nominal operation time - max

8 hour

Autonomy

1/3/8 hours

Material housing

Aluminium

Color housing

Grey

Material cover

Plastic, transparent

Labelling type

Other

Number Of Poles (Numeric)

6

Impact strength

IK10

Kind of luminaire

Safety and exit sign luminaire

Color temperature - max

6500 K

Color temperature - min

6500 K

Light distributor

Focal lens

Energy efficiency class of the built-in lamp

A++, A+, A (LED)

Function

Escape route lighting

Color of light

White

Color rendering index (CRI)

70

Luminaire With Limited Surface Temperature, Sign D

True

Number of lighting heads

1

Viewing distance

24 m

Data connection terminal

1.5 mm<sup>2</sup>

Frequency

50/60 Hz

Main connection terminal

2.5mm<sup>2</sup>

Testing system

CGLine +



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)