

Eaton 40071354879

Catalog Number: 40071354879

Eaton Outdoor Wall H, Safety lighting, Escape route, with battery heater for low temperature down to -20°C, CGLine + technology, LED, Maintained / Non-Maintained operation, IP65, 225lm, 1h/3h/8h selectable duration

General specifications



Product Name	Catalog Number
Eaton Outdoor Wall SC Emergency Luminaire	40071354879
	EAN
	4012539344537
Product Length/Depth	Product Height
303 mm	160 mm
Product Width	Product Weight
184 mm	2.66 kg
Certifications	
CE	

defaultTaxonomyAttributeLabel

Battery voltage

3.7 V

Battery quality

Lithium-ions

Glow wire test

850 °C

Protection class

I

Outdoor use compliance

True

Explosion protected

False

Degree of protection

IP65

Mode

Maintained / Non-Maintained (M / NM)

Lamp type

LED not exchangeable

With light source

True

Lamp holder

None

Lamp power

1.6 W

Monitoring equipment

Safety module for monitoring (central feeded system)

Power supply system

Peripheral (individual battery)

Voltage type

AC

Power factor

.91

Wiring system

Continuous circuit/emergency circuit

Resources

Catalogs

[eaton-el-cps-catalog-2020-gbr.pdf](#)

Certification reports

[eaton-emergency-lighting-self-contained-outdoor-wall-certificate-enec-en.pdf](#)

[eaton-emergency-lighting-self-contained-outdoor-wall-certificate-doc-en-fr-de.pdf](#)

Installation instructions

[eaton-emergency-lighting-self-contained-outdoor-wall-safety-instructions-all-lang.pdf](#)

Manuals and user guides

[eaton-emergency-lighting-self-contained-outdoor-wall-manual-en-de.pdf](#)

Technical data sheets

[eaton-emergency-lighting-self-contained-safety-outdoor-wall-datasheet-en.pdf](#)

Atlantic LED / Outdoor Wall CGLine+

With remote switch connection

True

Reserve-polarity protected

True

Conductor cross section

2.5

Connection type

Plug-in connection

Max. system power

9.3 W

Rated life time L70/B50 at 25 °C

50000 hour

Rated life time L90/B10 at 25 °C

50000 hour

Type of control gear

LED operating device current-controlled

Type of wiring

Suitable for through wiring

Nominal voltage AC - max

240 V

Nominal voltage AC - min

220 V

Apparent power at mains operation(NM)

9.2 VA

Effective power at mains operation (nm)

9.3 W

Rated ambient temp acc. IEC62722-2-1 - Min

-20 °C

Rated ambient temp acc. IEC62722-2-1 - Max

35 °C

Nominal operation time - min

1 hour

Nominal operation time - max

8 hour

Autonomy

1/3/8 hours

Mounting Method

Wall surface mounted

Material housing

Aluminium

Color housing

Grey

Material cover

Plastic, transparent

Labelling type

Other

Number Of Poles (Numeric)

6

Impact strength

IK10

Kind of luminaire

Safety luminaire for escape route and open area lighting

Rated Luminous Flux Acc. IEC 62722-2-1

250 lm

Color temperature - max

6500 K

Color temperature - min

6500 K

Light distributor

Focal lens

Energy efficiency class of the built-in lamp

A++, A+, A (LED)

Function

Escape route lighting

Color of light

White

Color rendering index (CRI)

70-79

Luminaire With Limited Surface Temperature, Sign D

True

Number of lighting heads

1

Data connection terminal

1.5 mm²

Frequency

50/60 Hz

Main connection terminal

2.5mm²

Testing system

CGLine +



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia