

# Eaton LUM16025RS

Catalog Number: LUM16025RS

Emergency Lighting Self-Contained; Ultraled 45 refurbished without baseplate.SATI;LED; 45lm, 1h, IP43, IK08

## General specifications

Livré sans patère



|                                       |                |
|---------------------------------------|----------------|
| Product Name                          | Catalog Number |
| Eaton refurbished emergency luminaire | LUM16025RS     |

|                                       |               |
|---------------------------------------|---------------|
| Model Code                            | EAN           |
| UltraLed 45 Reconditionné Sans patère | 3660191816674 |

|                      |                |
|----------------------|----------------|
| Product Length/Depth | Product Height |
| 214 mm               | 40 mm          |

|               |                |
|---------------|----------------|
| Product Width | Product Weight |
| 105 mm        | 0.326 kg       |

Certifications  
NF AEAS

## Battery voltage

3.6 V

## Battery quality

NiCd

## Glow wire test

850 °C

## Permissible ambient temperature - min

25 °C

## Permissible ambient temperature - max

25 °C

## Protection class

II

## Outdoor use compliance

False

## Explosion protected

False

## Degree of protection

IP43

## Mode

Maintained (M)

## Lamp type

LED not exchangeable

## With light source

True

## Lamp holder

None

## Type of indicator

Only single-sided

## Monitoring equipment

Automatic self test

## Power supply system

Peripheral (individual battery)

## Voltage type

AC

## Apparent Power At Mains Operation

2 VA

Power factor

.61

Wiring system

Continuous circuit/emergency circuit

With remote switch connection

True

Reserve-polarity protected

True

Conductor cross section

2.5

Connection type

Plug-in connection

Max. system power

1.2 W

Rated life time L80/B10 at 25 °C

51000 hour

Type of control gear

Not required

Nominal voltage AC - max

230 V

Nominal voltage AC - min

230 V

Rated ambient temp acc. IEC62722-2-1 - Min

5 °C

Rated ambient temp acc. IEC62722-2-1 - Max

40 °C

Nominal operation time - min

1 hour

Nominal operation time - max

1 hour

Autonomy

1h

Mounting Method

Wall surface mounted

Material housing

Plastic

Color housing

White

Material cover

Plastic, transparent

Labelling type

Insert sheet/plate

Pictogram included

True

Number Of Poles (Numeric)

2

Impact strength

IK08

Kind of luminaire

Exit sign luminaire

Rated Luminous Flux Acc. IEC 62722-2-1

45 lm

Color temperature - max

5000 K

Color temperature - min

5000 K

Light distributor

Reflector

Energy efficiency class of the built-in lamp

A++, A+, A (LED)

Function

Escape route signage

Color rendering index (CRI)

80

Luminous flux in standby mode

3 lm

Number of lighting heads

1

Suitable for number of lamps

2

Viewing distance

20 m

Frequency

50Hz

Product branding

Eaton

Number of LEDs

2

Shape

Rectangular

Application

Other

Testing system

SATI



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)