



Technical sheet

Recessed round LED fitting

Light fitting SPMN 1500, recessed, LED 830, prismatic cover, 190mm

Code: SPMN1500KN3/E190/ND

EAN: 8596099069445

This product contains a light source with energy efficiency class C



Luminaire properties

Product category:	Downlight/spot/floodlight	Effective luminous flux (lm):	1450
System power (W):	13	Luminaire efficacy (lm/W):	112
Rated lifetime L80/B50 (h):	80000	Degree of protection (IP):	IP54
Color housing:	White	Surface protection:	Powder coating
Material housing:	Steel		
Light source included:	Yes		
Suitable for built-in mounting:	Yes	Adjustability:	Not adjustable
Made in Czech republic:	Yes	Degree of protection II (IP):	IP20

Light source

Light source type:	LED	Color temperature (K):	3000
Color rendering index CRI:	80-89	Replaceability:	Removeable light source, replaceable ballast
Light source type:	1990480383004	Energy efficiency class:	C

Optical system

Optical system:	KN	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, structured

Dimensions

Outer diameter (mm):	210	Built-in diameter (mm):	190
Weight (kg):	0,9		

Electrical values

Protection class:	II	Nominal voltage (V):	220...240
No dim function:	Yes		