

LED panel for surface installation

MODUS Q, LED panel, surface, 600, LED 840, square A, driver 700mA

Code: QP3A600/700ND
EAN: 8595073791617



Luminaire properties

Product category:	Ceiling / wall luminaires	Effective luminous flux (lm):	4500
System power (W):	34	Luminaire efficacy (lm/W):	132
Rated lifetime L80/B50 (h):	80000	Degree of protection (IP):	IP40
Color housing:	Aluminium	Suitable for suspended mounting:	Yes
Material housing:	Aluminium		
Light source included:	Yes		
Suitable for built-in mounting:	Yes	Suitable for surface mounting:	Yes
Suitable for ceiling mounting:	Yes	Made in Czech republic:	Yes
Degree of protection II (IP):	IP20		

Light source

Light source type:	LED	Color temperature (K):	4000
Color rendering index CRI:	80-89	Replaceability:	Removeable light source, replaceable ballast

Optical system

Optical system:	KO	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, opal

Dimensions

Length (mm):	596	Width (mm):	596
Height/depth (mm):	60	Built-in height/depth (mm):	60
Raster (mm):	600	Size version:	S
Weight (kg):	5,9		

Electrical values

Protection class:	I	Connection type:	Pinching contact
Voltage type:	AC	Type of control gear:	LED operating device current-controlled
Nominal voltage (V):	220...240	Control gear included:	Yes
No dim function:	Yes		