

Luminaire with asymetrical reflector

MODUS ASTA 3000, asymetric reflector, 1200mm, surface/pendant, LED 840

Code: ASTAP3000M4/ND

EAN: 8596099044671

This product contains a light source with energy efficiency class C



Luminaire properties

Product category:	Ceiling / wall luminaires	Effective luminous flux (lm):	3200
System power (W):	25	Luminaire efficacy (lm/W):	128
Rated lifetime L80/B50 (h):	80000	Degree of protection (IP):	IP20
Color housing:	White	Suitable for suspended mounting:	Yes
Material housing:	Steel		
Light source included:	Yes		
Suitable for built-in mounting:	Yes	Suitable for surface mounting:	Yes
Suitable for ceiling mounting:	Yes	Made in Czech republic:	Yes

Light source

Light source type:	LED	Color temperature (K):	4000
Color rendering index CRI:	80-89	Replaceability:	Replaceable light source by professional, replaceable ballast
Light source type:	1990880184002	Energy efficiency class:	C

Optical system

Optical system:	AS	Light outlet:	Direct
Light sharing:	Asymmetric		

Dimensions

Length (mm):	1195	Width (mm):	100
Height/depth (mm):	60	Built-in height/depth (mm):	60
Raster (mm):	600	Size version:	M
Weight (kg):	3,3		

Electrical values

Protection class:	I	Connection type:	Pinching contact
Voltage type:	AC	Type of control gear:	LED operating device current-controlled
Nominal voltage (V):	220...240	Control gear included:	Yes
Type of wiring:	Ending	No dim function:	Yes