



## Surface louvre fitting

**MODUS LLL3000, 1x LED , 1510mm, MAT alu louvre , surface, LED 840, NONSELV 350mA**

**Code:** LLL3000RL1KVM4ND

**EAN:** 8596099002374

This product contains a light source with energy efficiency class C



## Luminaire properties

Product category:	<b>Ceiling / wall luminaires</b>	Effective luminous flux (lm):	<b>3500</b>
System power (W):	<b>30</b>	Luminaire efficacy (lm/W):	<b>117</b>
Rated lifetime L80/B50 (h):	<b>80000</b>	Degree of protection (IP):	<b>IP20</b>
Color housing:	<b>White</b>	Suitable for suspended mounting:	<b>Yes</b>
Material housing:	<b>Steel</b>		
Light source included:	<b>Yes</b>		
Suitable for surface mounting:	<b>Yes</b>	Suitable for ceiling mounting:	<b>Yes</b>
Made in Czech republic:	<b>Yes</b>		

## Light source

Light source type:	<b>LED</b>	Color temperature (K):	<b>4000</b>
Color rendering index CRI:	<b>80-89</b>	Replaceability:	<b>Removeable light source, replaceable ballast</b>
Light source type:	<b>1990420184003</b>	Energy efficiency class:	<b>C</b>

## Optical system

Optical system:	<b>KVM</b>	Light outlet:	<b>Direct</b>
Type of grid:	<b>Matt</b>	Anti-glare limiting UGR:	<b>19</b>
Light sharing:	<b>Symmetric</b>	Material cover:	<b>Plastic, opal</b>
Fit for monitor workplace:	<b>Yes</b>		

## Dimensions

Length (mm):	<b>1510</b>	Width (mm):	<b>153</b>
Height/depth (mm):	<b>52</b>	Size version:	<b>L</b>
Weight (kg):	<b>3,5</b>		

## Electrical values

Protection class:	<b>I</b>	Connection type:	<b>Pinching contact</b>
Voltage type:	<b>AC</b>	Type of control gear:	<b>LED operating device current-controlled</b>
Nominal voltage (V):	<b>220...240</b>	Control gear included:	<b>Yes</b>
No dim function:	<b>Yes</b>		