



Surface louvre fitting

MODUS LLL6000, 2x LED , 1510mm, MAT alu louvre , surface, LED 840, NONSELV 350mA, China free

Code: LLL6000RL2KVM4ND/EU

EAN: 8596099075460

This product contains a light source with energy efficiency class C



Luminaire properties

Product category:	Ceiling / wall luminaires	Effective luminous flux (lm):	7000
System power (W):	58	Luminaire efficacy (lm/W):	121
Rated lifetime L80/B50 (h):	80000	Degree of protection (IP):	IP20
Color housing:	White	Suitable for suspended mounting:	Yes
Material housing:	Steel		
Light source included:	Yes		
Suitable for surface mounting:	Yes	Suitable for ceiling mounting:	Yes
Made in Czech republic:	Yes		

Light source

Light source type:	LED	Color temperature (K):	4000
Color rendering index CRI:	80-89	Replaceability:	Removeable light source, replaceable ballast
Light source type:	1990420184003	Energy efficiency class:	C

Optical system

Optical system:	KVM	Light outlet:	Direct
Type of grid:	Matt	Anti-glare limiting UGR:	19
Light sharing:	Symmetric	Material cover:	Plastic, opal
Fit for monitor workplace:	Yes		

Dimensions

Length (mm):	1510	Width (mm):	238
Height/depth (mm):	52	Size version:	L
Weight (kg):	4		

Electrical values

Protection class:	I	Connection type:	Pinching contact
Voltage type:	AC	Type of control gear:	LED operating device current-controlled
Nominal voltage (V):	220...240	Control gear included:	Yes
No dim function:	Yes		

Without chinese components: **Yes**