



## LED waterproof light fitting

**MODUS PL 10000, wide body 1575mm, LED 840 , body PE, opal PC cover, IP65, driver 2100mA**

**Code:** PL10000L2W4ND

**EAN:** 8596099001995

This product contains a light source with energy efficiency class C



### Luminaire properties

Product category:	<b>Ceiling / wall luminaires</b>	Effective luminous flux (lm):	<b>11000</b>
System power (W):	<b>70</b>	Luminaire efficacy (lm/W):	<b>157</b>
Rated lifetime L80/B50 (h):	<b>80000</b>	Degree of protection (IP):	<b>IP65</b>
Color housing:	<b>Grey</b>	Impact strength:	<b>IK08</b>
Suitable for suspended mounting:	<b>Yes</b>		
Material housing:	<b>Plastic</b>		
Light source included:	<b>Yes</b>	Suitable for wall mounting:	<b>Yes</b>
Suitable for surface mounting:	<b>Yes</b>	Rated ambient temperature (°C):	<b>-10...+45</b>
Suitable for ceiling mounting:	<b>Yes</b>	Made in Czech republic:	<b>Yes</b>

### Light source

Light source type:	<b>LED</b>	Color temperature (K):	<b>4000</b>
Color rendering index CRI:	<b>80-89</b>	Replaceability:	<b>Replaceable light source by professional, replaceable ballast</b>
Light source type:	<b>1990660184005</b>	Energy efficiency class:	<b>C</b>

## Optical system

Optical system:	<b>CO</b>	Light outlet:	<b>Direct</b>
Light sharing:	<b>Symmetric</b>	Material cover:	<b>Plastic, opal</b>

## Dimensions

Length (mm):	<b>1575</b>	Width (mm):	<b>135</b>
Height/depth (mm):	<b>100</b>	Size version:	<b>L</b>
Weight (kg):	<b>2,8</b>		

## Electrical values

Protection class:	<b>I</b>	Voltage type:	<b>AC</b>
Type of control gear:	<b>LED operating device current-controlled</b>	Nominal voltage (V):	<b>220...240</b>
Control gear included:	<b>Yes</b>	No dim function:	<b>Yes</b>
Indoor use only:	<b>Yes</b>		