

Eaton EP-400211

Catalog Number: EP-400211

Eaton Moeller series SLC Stack light compact, Green, Yellow, Red, 24 V DC, Pulsed tone, Standard mounting

Photo is representative

General specifications

Product Name	Catalog Number
Eaton Moeller® series SLC Signal tower compact	EP-400211
	EAN
	4015082954918
Product Length/Depth	Product Height
70 mm	291 mm
Product Width	Product Weight
61 mm	0.226 kg
Certifications	Model Code
CE	SLC-100-RYG-AP-24



defaultTaxonomyAttributeLabel

Type

Complete device

Product Category

SL signal towers

Fitted with:

Push-in

Pollution degree

3

Alarm type

Pulsed tone

Connection to SmartWire-DT

No

Mounting Method

Standard stacklight base

Illumination

Continuous LED

Red blinking LED

Base

Standard

Decibel

70 dB

Ambient operating temperature - max

50 °C

Ambient operating temperature - min

-25 °C

Leakage current

0.003 A

Outside diameter

61 mm

Radiation angle

360 °

Rated operational voltage (Ue) - max

24 V

Rated operational voltage (Ue) - min

24 V

Resources

Declarations of conformity

[DA-DC-00004998.pdf](#)

[DA-DC-00004994.pdf](#)

Installation instructions

[eaton-operating-devices-stacklight-compact-slc-instruction-leaflet-il047032zu.pdf](#)

mCAD model

[eaton-slc-100-ryg-3d-model.stp](#)

[eaton-slc_100_ryg-drawing.dwg](#)

Color

Black tube
Green
Yellow
Red

Lens color

Green
Yellow
Red

Voltage type

DC

Material

UV Protected material

Mounting position

As required

Degree of protection

IP66
NEMA 4X

Overvoltage category

III

Lifespan, electrical

50,000 h

Light type

Continuous light
Red blinking light

Loudness

70 db

Light modules

LED

Number of modules

1

Rated operational voltage

24 V DC

Terminal capacity

Push-in 6-pole
up to 1,5mm² without plastic collar
up to 0,75mm² with plastic collar

Voltage type of operating voltage

DC

Operating voltage at AC, 50 Hz - min

0 V

Operating voltage at AC, 50 Hz - max

0 V

Operating voltage at AC, 60 Hz - min

0 V

Operating voltage at AC, 60 Hz - max

0 V

Operating voltage at DC - min

24 V

Operating voltage at DC - max

24 V

Color light 1

Green

Color light 2

Yellow

Color light 3

Red



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia