

Surface mounting enclosure, flat, 4 mounting locations, M22



Part no. M22-FI4 197234

EL Number 4300433

(Norway)

| General specifications | |
|----------------------------------|---|
| Product name | Eaton Moeller® series M22 Accessory Surface mounting enclosure |
| Part no. | M22-FI4 |
| EAN | 4015080893059 |
| Product Length/Depth | 279 millimetre |
| Product height | 44 millimetre |
| Product width | 43 millimetre |
| Product weight | 0.201 kilogram |
| Certifications | CE marking IEC/EN 60947-5 UL Category Control No.: NKCR CSA certified CSA file No. 012528 CSA-C22.2 No. 14-05 CSA Class No.: 3211-03 UL File No.: E29184 UL 508 CSA-C22.2 No. 94-91 UL Listed |
| Product Tradename | M22 |
| Product Type | Accessory |
| Product Sub Type | Surface mounting enclosure |
| Features & Functions | |
| Enclosure color | Gray |
| Enclosure material | Plastic |
| Fitted with: | High-grade steel screws |
| Knockouts | 2 x M20 (cable entry knockout at the side, 1 x each side) 1 x M20 (cable entry knockouts at the rear) |
| Number of locations | 4 |
| RAL-number | 7035 |
| General information | |
| Degree of protection | NEMA 4X IP67/IP69K |
| Opening diameter | 22.5 mm |
| Communication | |
| Connection to SmartWire-DT | No |
| Contacts | |
| Force for positive opening - min | 0 N |

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Enclosure for control circuit devices (EC000200)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Housing for command and alarm devices (ecl@ss13-27-37-12-05 [AKF023019])

| [AKF023019]) | | |
|-----------------------------|----|-------------------------|
| Number of command positions | | 4 |
| Construction type housing | | Surface mounted housing |
| Housing material | | Plastic |
| Housing material quality | | Other |
| Diameter openings | mm | 22.5 |
| Colour housing cover | | Grey |
| Degree of protection (IP) | | IP67/IP69K |
| Degree of protection (NEMA) | | 4X |
| Width | mm | 43 |
| Height | mm | 44 |

Depth mm 279