



Contactor, 24 V DC, 3 pole, 380 V 400 V, 4 kW, Contacts N/O = Normally open= 1 N/O, Spring-loaded terminals, DC operation

Part no. **DILEM-10-G-C(24VDC)**
230165

General specifications		
Product name		Eaton Moeller® series DILEM Mini contactor
Part no.		DILEM-10-G-C(24VDC)
EAN		4015082301651
Product Length/Depth		54 millimetre
Product height		58 millimetre
Product width		45 millimetre
Product weight		0.206 kilogram
Certifications		IEC/EN 60947-4-1 CSA CSA Class No.: 3211-04 VDE 0660 CSA File No.: 012528 CSA-C22.2 No. 14-05 UL Category Control No.: NLDX IEC/EN 60947 UL File No.: E29096 UL 508 CE UL
Product Tradename		DILEM
Product Type		Mini contactor
Product Sub Type		None
Catalog Notes		Also tested according to AC-3e.
Features & Functions		
Features		Positive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact module
Fitted with:		Auxiliary contact
General information		
Application		Mini Contactors for Motors and Resistive Loads
Degree of protection		IP20
Lifespan, mechanical		20,000,000 Operations 150,000 Operations (at 240 V, DC, L/R = 50 ms: 2 contacts in series 0.5 A) 200,000 Operations (at 240 V, AC-15)
Mounting position		As required (except vertical with terminals A1/A2 at the bottom)
Operating frequency		9000 mechanical Operations/h
Overvoltage category		III
Pollution degree		3
Product category		Contactors
Protection		Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
Rated impulse withstand voltage (Uimp)		6000 V AC
Shock resistance		20 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 8 g, N/O auxiliary contact, Basic unit without auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 20 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 10 g, N/O main contact, Basic unit without auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 10 g, N/O main contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
Suitable for		Also motors with efficiency class IE3
Utilization category		AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-4: Normal AC induction motors: starting, plugging, reversing, inching AC-3: Normal AC induction motors: starting, switch off during running
Voltage type		DC
Climatic environmental conditions		

Ambient operating temperature - min			-25 °C
Ambient operating temperature - max			50 °C
Ambient operating temperature (enclosed) - min			25 °C
Ambient operating temperature (enclosed) - max			40 °C
Ambient storage temperature - min			40 °C
Ambient storage temperature - max			80 °C
Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Terminal capacities			
Terminal capacity (flexible with ferrule)			2 x (1 - 2.5) mm ² 1 x (1 - 2.5) mm ²
Terminal capacity (solid/stranded AWG)			16 - 14
Stripping length (main cable)			10 mm
Screwdriver size			0.6 x 3.5 mm, Spring-loaded terminals
Electrical rating			
Rated breaking capacity at 220/230 V			90 A
Rated breaking capacity at 380/400 V			90 A
Rated breaking capacity at 500 V			64 A
Rated operational power at AC-3, 240 V, 50 Hz			2.5 kW
Rated operational power at AC-3, 380/400 V, 50 Hz			4 kW
Rated operational power at AC-3, 415 V, 50 Hz			4.3 kW
Rated breaking capacity at 660/690 V			42 A
Rated making capacity up to 440 V (cos phi to IEC/EN 60947)			110 A
Rated operational power at AC-4, 220/230 V, 50 Hz			1.5 kW
Rated operational power at AC-4, 240 V, 50 Hz			1.8 kW
Rated operational power at AC-4, 415 V, 50 Hz			3.1 kW
Rated operational power at AC-4, 440 V, 50 Hz			3.3 kW
Rated operational power at AC-4, 500 V, 50 Hz			3 kW
Rated operational power at AC-4, 660/690 V, 50 Hz			3 kW
Rated operational voltage (Ue) at AC - max			690 V
Rated insulation voltage (Ui)			690 V
Rated operational current (Ie)			0.5 A at 220 V, DC L/R ≤ 15 ms (with 3 contacts in series) 1.5 A at 100 V, DC L/R ≤ 15 ms (with 3 contacts in series) 2.5 A at 24 V, DC L/R ≤ 15 ms (with 1 contact in series) 2.5 A at 60 V, DC L/R ≤ 15 ms (with 2 contacts in series)
Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V			22 A
Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V			6 A
Rated operational current (Ie) at AC-15, 380 V, 400 V, 415 V			3 A
Rated operational current (Ie) at AC-15, 500 V			1.5 A
Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V			9 A
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V			9 A
Rated operational current (Ie) at AC-3, 440 V			9 A
Rated operational current (Ie) at AC-3, 500 V			6.4 A
Rated operational current (Ie) at AC-3, 660 V, 690 V			4.8 A
Rated operational current (Ie) at AC-4, 220 V, 230 V, 240 V			6.6 A
Rated operational current (Ie) at AC-4, 440 V			6.6 A
Rated operational current (Ie) at AC-4, 500 V			5 A
Rated operational current (Ie) at AC-4, 660 V, 690 V			3.4 A
Rated operational current (Ie) at DC-1, 110 V			20 A
Rated operational current (Ie) at DC-1, 12 V			20 A
Rated operational current (Ie) at DC-1, 220 V			20 A
Rated operational current (Ie) at DC-1, 24 V			20 A
Rated operational current (Ie) at DC-1, 60 V			20 A
Safe isolation			300 V AC, Between coil and auxiliary contacts, According to EN 61140 300 V AC, Between the contacts, According to EN 61140 300 V AC, Between auxiliary contacts, According to EN 61140 300 V AC, Between coil and contacts, According to EN 61140
Short-circuit rating			

Short-circuit current rating (basic rating)		5 kA, SCCR (UL/CSA) 45 A, max. Fuse, SCCR (UL/CSA)
Short-circuit protection		10 A fast, Max. Fuse 500V, Auxiliary contacts, Short-circuit rating without welding PKZM0-4, Maximum overcurrent protective device, Short-circuit protection only, Auxiliary contacts, Short-circuit rating without welding 6 A gG/gL, Max. Fuse 500V, Auxiliary contacts, Short-circuit rating without welding
Short-circuit protection rating (type 1 coordination) at 500 V		20 A gG/gL
Short-circuit protection rating (type 2 coordination) at 500 V		10 A gG/gL
Conventional thermal current Ith		
Conventional thermal current Ith (1-pole, enclosed)		40 A
Conventional thermal current Ith (3-pole, enclosed)		16 A
Conventional thermal current Ith at 55°C (3-pole, open)		19 A
Conventional thermal current Ith of auxiliary contacts (1-pole, open)		10 A
Conventional thermal current Ith of main contacts (1-pole, open)		50 A
Switching capacity		
Switching capacity (main contacts, general use)		15 A, Maximum motor rating (UL/CSA)
Switching capacity (auxiliary contacts, general use)		10 A, 600 V AC, (UL/CSA) 0.5 A, 250 V DC, (UL/CSA)
Switching capacity (auxiliary contacts, pilot duty)		A600, AC operated (UL/CSA) P300, DC operated (UL/CSA)
Magnet system		
Arcing time		12 ms at 690 V AC
Changeover time		40 - 50 ms
Duty factor		100 %
Pick-up voltage		0.8 - 1.1 V DC x U _c
Power consumption		Smoothed DC voltage or three-phase bridge rectifier 2.3 VA/W at DC (Pick-up/Sealing power)
Rated control supply voltage (Us) at AC, 50 Hz - min		0 V
Rated control supply voltage (Us) at AC, 50 Hz - max		0 V
Rated control supply voltage (Us) at AC, 60 Hz - min		0 V
Rated control supply voltage (Us) at AC, 60 Hz - max		0 V
Rated control supply voltage (Us) at DC - min		24 V
Rated control supply voltage (Us) at DC - max		24 V
Switching time (AC operated, N/O, with auxiliary contact module, closing delay)		70 ms
Switching time (DC operated, make contacts, closing delay) - min		26 ms
Switching time (DC operated, make contacts, closing delay) - max		35 ms
Switching time (DC operated, make contacts, opening delay) - min		15 ms
Switching time (DC operated, make contacts, opening delay) - max		25 ms
Motor rating		
Assigned motor power at 115/120 V, 60 Hz, 1-phase		0.5 HP
Assigned motor power at 200/208 V, 60 Hz, 3-phase		2 HP
Assigned motor power at 230/240 V, 60 Hz, 1-phase		1.5 HP
Assigned motor power at 230/240 V, 60 Hz, 3-phase		3 HP
Assigned motor power at 460/480 V, 60 Hz, 3-phase		5 HP
Assigned motor power at 575/600 V, 60 Hz, 3-phase		5 HP
Contacts		
Control circuit reliability		< 2 λ, < 1 failure at 100,000,000 Operations (at U# = 24 V DC, U _{min} = 17 V, I _{min} = 5.4 mA)
Number of auxiliary contacts (normally closed contacts)		0
Number of auxiliary contacts (normally open contacts)		1
Design verification		
Equipment heat dissipation, current-dependent P _{vid}		0.9 W
Heat dissipation capacity P _{diss}		0 W
Heat dissipation per pole, current-dependent P _{vid}		0.3 W
Rated operational current for specified heat dissipation (I _n)		9 A
Static heat dissipation, non-current-dependent P _{vs}		2.3 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss13-27-37-10-03 [AAB718020])		
Rated control supply voltage AC 50 Hz	V	0 - 0
Rated control supply voltage AC 60 Hz	V	0 - 0
Rated control supply voltage DC	V	24 - 24
Voltage type for actuating		DC
Number of normally closed contacts as main contact		0
Number of normally open contacts as main contact		3
Type of electrical connection of main circuit		Spring clamp connection
Operating voltage AC 50 Hz	V	24 - 690
Operating voltage AC 60 Hz	V	24 - 690
Rated operation current I _e at AC-1, 400 V	A	22
Rated operation current I _e at AC-3, 400 V	A	9
Rated operation power at AC-3, 400 V	kW	4
Rated operation current I _e at AC-4, 400 V	A	6.6
Rated operation power at AC-4, 400 V	kW	3
Rated operation power NEMA	kW	3.7
Number of auxiliary contacts as normally open contact		1
Number of auxiliary contacts as normally closed contact		0
Modular version		No
Width	mm	45
Height	mm	58
Depth	mm	54