



LED linear fitting with optics

MODUS TOP6000, lenght 1415mm, LED 840, optic wide beam 60, no dimmable

Code: TOP6000L4CW/ND

EAN: 8596099031411

This product contains a light source with energy efficiency class C, D



Luminaire properties

| | | | |
|----------------------------|-------------------------|-------------------------------|--------------|
| Product category: | Batten luminaire | Effective luminous flux (lm): | 5800 |
| System power (W): | 37 | Rated lifetime L80/B50 (h): | 80000 |
| Degree of protection (IP): | IP20 | Color housing: | White |
| Material: | Steel | Light source included: | Yes |
| Made in Czech republic: | Yes | | |

Light source

| | | | |
|----------------------------|----------------------|--------------------------|--|
| Light source type: | LED | Color temperature (K): | 4000 |
| Color rendering index CRI: | 80-89 | Replaceability: | Replaceable light source by professional, replaceable ballast |
| Light source type: | 1990600184009 | Energy efficiency class: | C |
| Light source type: | 1990900184006 | Energy efficiency class: | D |

Optical system

| | | | |
|-----------------|-----------|--------------------|-----------------------|
| Optical system: | CW | Light distributor: | Refractor lens |
|-----------------|-----------|--------------------|-----------------------|

Dimensions

| | | | |
|--------------------|-------------|---------------|-----------|
| Length (mm): | 1415 | Width (mm): | 46 |
| Height/depth (mm): | 46 | Size version: | L |
| Weight (kg): | 2 | | |

Electrical values

| | | | |
|------------------------|--|----------------------|-----------|
| Protection class: | I | Voltage type: | AC |
| Type of control gear: | LED operating device current-controlled | Nominal voltage (V): | 220...240 |
| Control gear included: | Yes | No dim function: | Yes |