




Loop XL 3D

IP20 8W/865 650lm WH

Loop XL 3D Table lamp 8W 6500K 650lm No dim;
Protection cl. II; L70B50 20000h; LED not
exchangeable; CRI>80; Housing Steel; Colour wh;
Cover Glass transparent

IP20 8W/865 650lm WH

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
9610508	A7GALI	2.525	Loop XL 3D



IP20 8W/865 650lm WH

EC000302

Mounting	
Type of luminaire	Magnifier luminaire
Mounting method	Clamping
Suitable for wall mounting	No
Fit for workplace acc. EN 12464-1	No
Electrical connection with connector system	Yes

Structure	
Adjustable	Yes
Bendable	Yes
Adjustable height	Yes
Lamp type	LED not exchangeable
With lamp	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Steel
Housing colour	White
Cover material	Glass transparent
Cover colour	White
Control gear included	No
With switch	Yes
With socket outlet	No
Energy efficiency class of light source according to EU regulation 2019/2015	F

Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming DSI	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	No
Dimming phase cut-on	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
With dimmer	No

Photometric data	
Effective luminous flux (lm)	650
Colour of light (alphanumeric)	White
Colour temperature (min) (K)	6500
Colour temperature (max) (K)	6500
Colour rendering index CRI	80-89
Colour consistency (McAdam ellipse)	SDCM6
Colour temperature switchable	No

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	20000

Measurements	
Width (mm)	260
Height/depth (mm)	820
Length (mm)	260

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Protection class	II
Suitable for lamp power (min) (W)	8
Suitable for lamp power (max) (W)	8
Maximum system power (W)	8