


Loop Clip 3D IP20 6W/865 480lm WH

Loop Clip 3D Table lamp 6W 6500K 480lm No dim; Protection cl. III; L70B50 25000h; LED not exchangeable; CRI>80; Housing Steel; Colour wh; Cover Glass transparent

| IP20 6W/865 480lm WH | | | | |
|----------------------|--------|------|----------------|--|
| PRODUCT CODE | CODE | KG | PRODUCT FAMILY | |
| 9610509 | A7GALJ | 0.52 | Loop Clip 3D | |





IP20 6W/865 480lm WH

EC000302

| Mounting | |
|---|--------------------------|
| Type of luminaire | Magnifier lumi- naire |
| Mounting method | Clamping |
| Suitable for wall mounting | No |
| Fit for workplace acc. EN 12464-1 | No |
| Electrical connection with connector system | Yes |

| Structure | |
|--|---------------------------|
| Adjustable | Yes |
| Bendable | Yes |
| Adjustable height | Yes |
| Lamp type | LED not exchan- geable |
| With lamp | Yes |
| Suitable for number of lamps | 1 |
| Lamp holder | Other |
| Housing material | Steel |
| Housing colour | White |
| Cover material | Glass transpa- rent |
| Cover colour | White |
| Control gear included | No |
| With switch | Yes |
| With socket outlet | No |
| Energy efficiency class of light source according to EU regulation 2019/2015 | F |
| | |

| Dimming and control | |
|---|-----|
| Dimming 0-10 V | No |
| Dimming 1-10 V | No |
| Dimming DALI | No |
| Dimming DMX | No |
| Dimming DSI | No |
| Dimming potentiometer (integrated) | No |
| Dimming LineSwitch | No |
| Dimming manufacturer's proprietary system | No |
| Dimming mains voltage modulation | No |
| Dimming phase cut-off | No |
| Dimming phase cut-on | No |
| Dimming programmable | No |
| Dimming RF | No |
| Dimming Sine Wave Reduction | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming with push-button | No |
| No dimming function | Yes |
| With dimmer | No |

| Photometric data | |
|-------------------------------------|-------|
| Effective luminous flux (lm) | 480 |
| Colour of light (alphanumeric) | White |
| Colour temperature (min) (K) | 6500 |
| Colour temperature (max) (K) | 6500 |
| Colour rendering index CRI | 80-89 |
| Colour consistency (McAdam ellipse) | SDCM6 |
| Colour temperature switchable | No |

| Lifetime and capacity | |
|--------------------------------------|-------|
| Rated life time L70/B50 at 25 °C (h) | 25000 |

| Measurements | |
|-------------------|-----|
| Width (mm) | 125 |
| Height/depth (mm) | 350 |
| Length (mm) | 125 |

| Electrotechnical data | |
|-----------------------------------|-------|
| Voltage type | AC/DC |
| Nominal voltage (min) (V) | 100 |
| Nominal voltage (max) (V) | 240 |
| Protection class | III |
| Suitable for lamp power (min) (W) | 6 |
| Suitable for lamp power (max) (W) | 6 |
| Maximum system power (W) | 6 |
| | |

