

227402301310

Modular contactor



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

BROWSE PRODUCT PAGE

Technical Features:

Ambient temperature range:	-25...70 °C
Commercial description:	32 A modular contactor – 4 pole. 4 NO, 3 NO + 1 NC, 2 NO + 2 NC, 4 NC. NO and NC contact gap e 3 mm, double break, continuous duty for the coil and contacts, AC/DC silent coil (with varistor protection). Complies with EN 61095: 2009.
Contact configuration:	4 pole, NO
Dimensions:	35x85x60.4 mm
Electrical life:	150000 cycles
Insulation coil/contacts:	4 kV
Nominal voltage:	230 V
Operating range ac:	195.5...253 V
Operating range dc:	195.5...253 V
Rated contact voltage:	230 V AC
Rated current (contacts):	32 A
Supply:	AC/DC
Certifications and quality approvals (according to type):	<div><div>C</div><div>CE</div><div>EAC</div><div><div>c</div><div>UL</div><div>US</div></div><div>UK</div><div>CA</div></div>

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form the basis of a contract.

Need more information?

[Contact our sales](#) [Find a dealer](#)