

Eaton 229015

Catalog Number: 229015

Eaton Moeller® series M22 Acoustic device, compact, IP40_x

General specifications



Product Name	Catalog Number
Eaton Moeller® series M22 Accessory Acoustic indicator	229015
	Model Code
	M22-AMC
EAN	Product Length/Depth
4015082290153	62 mm
Product Height	Product Width
30 mm	30 mm
Product Weight	Compliances
0.024 kg	CE Marked
Certifications	Catalog Notes
CSA Std. C22.2 No. 94-91 UL 508 IEC 60947-5 EN 60947-5 CSA Std. C22.2 No. 14-05 VDE CSA-C22.2 No. 94-91 CSA-C22.2 No. 14-05 UL Category Control No.: NKCR CE CSA File No.: 012528 IEC/EN 60947 VDE 0660 IEC/EN 60947-5 CSA Class No.: 3211-03 UL File No.: E29184 UL CSA	without buzzer

Features & Functions

Color

Black

Fitted with:

BA 9s lamp socket

Loudness

0 dB

General

Degree of protection

IP40

NEMA 4X, 13

Overvoltage category

III

Pollution degree

3

Product Category

Accessories

Rated impulse withstand voltage (Uimp)

4000 V AC

Type

Compact

Voltage type

AC/DC

Ambient conditions, mechanical

Mounting position

As required

Shock resistance

Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Climatic environmental conditions

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

70 °C

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Terminal capacities

Terminal capacity (solid)

2 x (0.5 - 1.5) mm²

Terminal capacity (stranded)

0.5 - 1.5 mm²

Electrical rating

Rated insulation voltage (Ui)

250 V

Rated operational voltage (Ue) at AC - max

0 V

Rated operational voltage (Ue) at AC - min

0 V

Rated operational voltage (Ue) at DC - max

0 V

Rated operational voltage (Ue) at DC - min
0 V

Communication

Connection to SmartWire-DT
No

Contacts

Force for positive opening - min
0 N

Resources

- Catalogues
- [eaton-rmq-titan-brochure-br047004en-en-us.pdf](#)
 - [eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf](#)
 - [Flip catalog - Product Range Catalog - Command and indication](#)
- Certification reports
- [DA-DC-00004135.pdf](#)
 - [DA-DC-00004157.pdf](#)
- Drawings
- [eaton-operating-acoustic-m22-acoustic-device-dimensions.eps](#)
 - [eaton-general-m22-symbol.eps](#)
 - [eaton-general-m22-standards.eps](#)
 - [eaton-general-approval-m22-symbol.eps](#)
- eCAD model
- [DA-CE-ETN.M22-AMC](#)
- Installation instructions
- [IL04716002Z](#)
- Installation videos
- [RMQ Flat Design](#)
- mCAD model
- [DA-CD-akustikmelder](#)
 - [DA-CS-akustikmelder](#)
 - [eaton-akustikmelder-3d-model.stp](#)
- Multimedia
- [easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator](#)
 - [RMQ small E-Stop emergency-stop button](#)
 - [MCI MultiColor Light Indicator RMQ compact solution](#)
 - [MCI Multicolor Light Indicator M22 with SmartWire-DT](#)
- Sales notes
- [eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf](#)

[eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf](#)

[eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf](#)

[eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf](#)

[System overview](#)

[Pilot devices - selection aid](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia