

# Eaton 216628

Catalog Number: 216628

Eaton Moeller® series M22 Pushbutton, RMQ-Titan, Flat, maintained, red, inscribed, Bezel: titanium

### General specifications



Product Name	Catalog Number
Eaton Moeller® series M22 Pushbutton	216628
Model Code	EAN
M22-DR-R-X0	4015082166281
Product Length/Depth	Product Height
30 mm	30 mm
Product Width	Product Weight
30 mm	0.011 kg

### Certifications

CSA Class No.: 3211-03  
CSA File No.: 012528  
IEC/EN 60947-5  
UL 508  
UL Category Control No.: NKCR  
CSA-C22.2 No. 14-05  
UL File No.: E29184  
CE  
UL  
IEC/EN 60947  
CSA-C22.2 No. 94-91  
VDE 0660  
CSA  
DNV  
GL  
LR

## Features & Functions

### Bezel color

Titanium

### Bezel material

Plastic

### Design

Flat

Classical

### Features

Labelled

### Fitted with:

Front ring

### Functions

Stay-put/spring-return function can be changed on device

### Inscription

Inscribed

## General

### Degree of protection

IP66

NEMA 3R

NEMA 12

NEMA 13

NEMA 4X

IP67

IP69K

### Degree of protection (front side)

IP67/IP69K

NEMA 4X

### Lifespan, mechanical

1,000,000 Operations (AC operated)

### Opening diameter

22.5 mm

### Operating frequency

1800 Operations/h

### Product category

RMQ-Titan

### Size

Front dimensions: 22 x 22 mm

### Type

Pushbutton actuator

## Ambient conditions, mechanical

### Mounting position

As required

### Shock resistance

Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

## Climatic environmental conditions

### Ambient operating temperature - min

-25 °C

### Ambient operating temperature - max

70 °C

### Ambient storage temperature - min

40 °C

### Ambient storage temperature - max

80 °C

### Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

## Communication

Connection to SmartWire-DT

With SWD-RMQ connections

Yes

## Actuator

Actuating force

5 N

Actuator color

Red

Actuator function

Maintained

Switching function latching

## Contacts

Force for positive opening - min

0 N

## Design verification

Equipment heat dissipation, current-dependent P<sub>vid</sub>

0 W

Heat dissipation capacity P<sub>diss</sub>

0 W

Heat dissipation per pole, current-dependent P<sub>vid</sub>

0 W

Rated operational current for specified heat dissipation (I<sub>n</sub>)

0 A

Static heat dissipation, non-current-dependent P<sub>vs</sub>

0 W

### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

### 10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be

evaluated.

#### 10.2.7 Inscriptions

Meets the product standard's requirements.

#### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

#### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### 10.10 Temperature rise

Not applicable.

#### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Resources

### Catalogues

[eaton-rmq-titan-brochure-br047004en-en-us.pdf](#)

[Flip catalog - Product Range Catalog - Command and indication](#)

[eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf](#)

### Certification reports

[DA-DC-00004157.pdf](#)

[DA-DC-00004135.pdf](#)

### Drawings

[eaton-operating-pushbutton-m22-dimensions-004.eps](#)

[eaton-operating-pushbutton-m22-dimensions-003.eps](#)

[eaton-operating-actuation-m22-dimensions-002.eps](#)

[eaton-general-approval-m22-symbol.eps](#)

[eaton-operating-samrtwire-m22-3d-drawing.eps](#)

[116C079](#)

[eaton-general-m22-standards.eps](#)

[eaton-general-m22-symbol.eps](#)

### eCAD model

[ETN.216628.edz](#)

### Installation instructions

[IL04716002Z](#)

### Installation videos

[RMQ Flat Design](#)

### mCAD model

[DA-CS-drucktaste\\_flach](#)

[DA-CD-drucktaste\\_flach](#)

### Multimedia

[MCI Multicolor Light Indicator M22 with SmartWire-DT](#)

[easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator](#)

[RMQ small E-Stop emergency-stop button](#)

[MCI MultiColor Light Indicator RMQ compact solution](#)

### Sales notes

[eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf](#)

[eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf](#)

[eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf](#)

[System overview](#)

[Pilot devices - selection aid](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
[Eaton.com](#)

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](#)