

227202301410

Modular contactor



*This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.*

Technical description:

Modular contactor, 32 A, 2 pole, NC, 32 A, AgNi, AC/DC coil, 230 V, operating from 195.5 to 253 V (AC)/(DC), rated power 2.1 VA (AC)/(DC), holding voltage 195.5 V (AC)/(DC), must drop-out voltage 46 V (AC)/(DC), option: Mechanical indicator, ambient temperature from -15 to +55 °C

BROWSE PRODUCT PAGE

Technical Features:

Ambient temperature range:	-15...55 °C
Commercial description:	32 A modular contactor – 2 pole. 17.5 mm wide, contact material AgNi. NO and NC contact gap e 3 mm, double break, continuous duty for the coil and contacts, AC/DC silent coil (with varistor protection). Complies with EN 61095: 2009.
Contact configuration:	2 pole, NC
Dimensions:	17.5x85x60.4 mm
Electrical life:	100000 cycles
Insulation coil/contacts:	4 kV
Nominal voltage:	230 V
Operating range ac:	195.5...253 V
Operating range dc:	195.5...253 V
Rated contact voltage:	230 V AC
Rated current (contacts):	32 A
Supply:	AC/DC
Certifications and quality approvals (according to type):	<div><div>C</div><div>CE</div><div>EAC</div><div><div>c</div><div>UL</div><div>US</div></div><div>UK</div><div>CA</div></div>

The information, technical details, data and features contained in this document are subject to change or modification at any time.  
It is for information purposes only and does not form the basis of a contract.

Need more information?

[Contact our sales](#) [Find a dealer](#)