

223402304320

Modular contactor



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:

Modular contactor, 25 A, 4 pole, NO, 25 A, AgSnO2, AC/DC coil, 230 V, operating from 184 to 264 V (AC) e da 176 to 242 V (DC), rated power 2 VA (AC) / 2.2 W (DC), holding voltage 92 V (AC)/(DC), must drop-out voltage 23 V (AC)/(DC), option: Mechanical indicator + LED, ambient temperature from -25 to +50 °C

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-25...50 °C
Commercial description:	Modular contactor 25 A - 4 contacts, 35mm width and a NO contact gap e 3 mm, double break. Type 22.34 complies with EN 61095: 2009
Contact configuration:	4 pole, NO
Dimensions:	35x84x56.5 mm
Electrical life:	30000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage:	230 V
Operating range ac:	184...264 V
Operating range dc:	176...242 V
Rated contact voltage:	250 V AC
Rated current (contacts):	25 A
Supply:	AC/DC

Certifications and quality approvals (according to type):



The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form the basis of a contract.

Need more information?
[Contact our sales](#) [Find a dealer](#)