



Low voltage NH fuse

EL Number
(Norway)

400NHG2B
1664074

General specifications

Product name	Eaton Bussmann series low voltage NH Fuse
Part no.	400NHG2B
EAN	5027590479776
Product Length/Depth	150 millimetre
Product height	71 millimetre
Product width	54 millimetre
Product weight	659 gram
Compliances	CE Marked RoHS Compliant
Certifications	IEC 60269-1 IEC 60269-2 DIN 43620
Product Tradename	None
Product Type	Low voltage NH fuse
Product Sub Type	None

Electrical data

Amperage Rating	400 A
Voltage rating	500 V
Voltage type	AC
Breaking capacity	120 kA
Class	Class gG/gL
Frequency rating - min	45 Hz
Frequency rating - max	62 Hz

Product specifications

Fuse size	NH2
Insulated metal gripping lugs (IMGL)	No

Accessories

Suitable for	EBH Size 00 to 4 Horizontal fuse switch-disconnectors Microswitch 170H0236 Microswitch 170H0235 TD2-D Tripe pole NH Fuse base SD2-D Single pole NH Fuse base
--------------	--

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])		
Construction size		NH2
Nominal rated current	A	400
Nominal rated voltage	V	500
Utilization category		gL/gG (cable protection/equipment protection)
Type of fuse status indicator		Combination fuse status indicator