

DATASHEET - C10-SLS/32/3



Fuse disconnectors, 32A, 3 p, 10 x 38

Part no. C10-SLS/32/3
112223

General specifications		
Product name		Eaton Distribution parts
Part no.		C10-SLS/32/3
EAN		4015081117819
Product Length/Depth		85 millimetre
Product height		70.8 millimetre
Product width		52.5 millimetre
Product weight		0.18 kilogram
Compliances		RoHS conform
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
PDH Status		Active
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Actuator position		Front side
Actuator type		Other
Cable entry type		Other
Conditioned rated short-circuit current Iq		100 kA
Degree of protection (front side)		IP20
Electrical connection type of main circuit		Screw connection
Number of poles		Three-pole
Power rating at AC-23, 400 V		0 kW
Rated conditional short-circuit current (Iq)		100 kA
Rated operating voltage (Ue) at AC - max		690 V
Rated operation power at AC-23, 400 V		0 kW
Rated short-time withstand current (Icw)		0.3 kA
Rated uninterrupted current (Iu)		32 A
Suitable for		Ground mounting
Suitable for fuses		Shape C1-C3

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ecI@ss13-27-37-14-01 [AKF058018])		
Version as main switch		No
Version as safety switch		No
Max. rated operation voltage Ue AC	V	690
Rated permanent current Iu	A	32
Rated operation power at AC-23, 400 V	kW	0
Conditioned rated short-circuit current Iq	kA	100
Rated short-time withstand current Icw	kA	0.3
Suitable for fuses		Shape C1-C3
Number of poles		3
With error protection		No
Type of electrical connection of main circuit		Screw connection
Cable entry		Other

Equipped with connectors		No
Suitable for floor mounting		Yes
Suitable for front mounting		No
Suitable for busbar mounting		No
Type of control element		Other
Position control element		Front side
Motor drive optional		No
Motor drive integrated		No
Version as emergency stop installation		No
Degree of protection (IP), front side		IP20