



Fuse-link, LV, 4 A, AC 500 V, 10 x 38 mm, gL/gG, IEC

EL Number
(Norway)

C10G4
1600331

General specifications			
Product name			Eaton Bussmann series low voltage cylindrical fuse
Part no.			C10G4
EAN			5027590493543
Product Length/Depth			38 millimetre
Product height			10 millimetre
Product width			10 millimetre
Product weight			8.2 gram
Compliances			GoST-R CE Marked RoHS Compliant
Certifications			IEC 60269
Product Tradename			None
Product Type			Low voltage cylindrical fuse
Product Sub Type			None
Electrical data			
Amperage Rating			4 A
Voltage rating			500 V
Voltage type			AC
Breaking capacity			120 kA
Utilization category			gG (cable protection/equipment protection)
Compatible fuse holder			
Suitable for			CHM Modular fuse holder

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss13-27-14-20-02 [AFZ797018])			
Model			Ceramic fuse
Size			10x38 mm
Voltage type			AC
Rated current		A	4
Rated voltage		V	500
Utilization category			gG (cable protection/equipment protection)
Rated operating frequency		Hz	45 - 62
Type of fuse status indicator			Other
Release characteristic			Other
Breaking capacity		kA	120
Power loss at rated current		W	0.7