

Eaton C10M20

Catalog Number: C10M20

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 400 Volts AC, 20 Amps, 120 kA Breaking capacity, class aM, without indicator, compatible with a CHM Modular fuse holder



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C10M20
	Model Code
	CYLINDRICAL FUSE 10 x 38 20A AM 400V AC
UPC	EAN
051712754613	5027590493680
Product Length/Depth	Product Height
38 mm	10 mm
Product Width	Product Weight
10 mm	8.2 g
Warranty	Compliances
1 year limited	CE Marked
	GoST-R
	RoHS Compliant
Certifications	
IEC 60269	

Product specifications

Type

fuse

Application

motor protection
for industrial applications

Amperage Rating

20 A

Fuse size

10 x 38 mm

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated voltage AC

400 V

Class

Class aM

Fuse type

C10M

Utilization category

aM (switchgear protection)

Fuse indicator

Other

Watt losses

0.96 W

Connection

Ferrule end x ferrule end

Construction size

10 mm x 38 mm

Fuse shape

Resources

Catalogs

[CA134002EN](#)

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[CE C08G, C08M, etc cylindrical fuselinks](#)

[UKCA C08G, C08M, etc cylindrical fuselinks](#)

Technical data sheets

[720115 Cylindrical fuses](#)

Cylindrical

Voltage type

AC

Suitable for

CHM Modular fuse holder

Material

Ceramic

Release characteristic

Other

Quantity

10

Voltage rating

400 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia