

Eaton C10M16

Catalog Number: C10M16

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 16 Amps, 120 kA Breaking capacity, class aM, without indicator, compatible with a CHM Modular fuse holder



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C10M16
	UPC
	051712754606
EAN	Product Length/Depth
5027590493666	38 mm
Product Height	Product Width
10 mm	10 mm
Product Weight	Warranty
8.2 g	1 year limited
Compliances	Certifications
CE Marked	IEC 60269
GoST-R	
RoHS Compliant	

Product specifications

Type

fuse

Application

motor protection
for industrial applications

Amperage Rating

16 A

Fuse size

10 x 38 mm

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated voltage AC

500 V

Class

Class aM

Fuse type

C10M

Utilization category

aM (switchgear protection)

Fuse indicator

Other

Watt losses

0.92 W

Connection

Ferrule end x ferrule end

Construction size

10 mm x 38 mm

Fuse shape

Resources

Catalogs

CA134002EN

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[UKCA C08G, C08M, etc cylindrical fuselinks](#)

[CE C08G, C08M, etc cylindrical fuselinks](#)

Technical data sheets

[720115 Cylindrical fuses](#)

Cylindrical

Voltage type

AC

Suitable for

CHM Modular fuse holder

Material

Ceramic

Release characteristic

Other

Quantity

10

Voltage rating

500 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia