



Base module;400-mm aluminum tube and foot

Part no. SL4-PIB-400
171299
EL Number 4137535
(Norway)

General specifications		
Product name		Eaton Moeller® series SL4 Base module
Part no.		SL4-PIB-400
EAN		4015081678426
Product Length/Depth		72 millimetre
Product height		452 millimetre
Product width		72 millimetre
Product weight		0.214 kilogram
Certifications		CSA Class No.: NKCR7 UL Certified by UL for use in Canada UL Category Control No.: NKCR CSA-C22.2 No. 94-91 UL report applies to both US and Canada UL File No.: E29184 IEC/EN 60529 IEC/EN 60947-5-1 UL 508 CE CSA-C22.2 No. 14-10
Product Tradename		SL4
Product Type		Base module
Product Sub Type		None
Features & Functions		
Color		Other
Fitted with:		Cover Plastic foot Aluminum tube
Number of modules		Max. 5 (with standard base) Max. 10 (with base for mounting on both sides) Max. 5
General information		
Connection to SmartWire-DT		No
Degree of protection		NEMA 13 NEMA 4 NEMA 4X IP66
Mounting Method		Bracket Floor Horizontal
Mounting position		As required
Overvoltage category		III
Pollution degree		3
Product Category		SL signal towers
Rated impulse withstand voltage (Uimp)		4000 V AC
Shock resistance		Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Tube length		400 mm
Type		Base module
Climatic environmental conditions		
Ambient operating temperature - min		-30 °C
Ambient operating temperature - max		60 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Terminal capacities		
Terminal capacity (AWG)		24 - 16

Terminal capacity (flexible with ferrule and plastic collar)			0.25 - 0.75 mm²
Terminal capacity (solid/flexible)			0.2 - 1.5 mm²
Terminal capacity (solid/flexible with ferrule)			0.25 - 1.5 mm²
Electrical rating			
Rated insulation voltage (Ui)			250 V
Rated operational voltage			24 V AC/DC ± 10 % 230/240 V AC ± 10 % 110/120 V AC ± 10 %

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Connection module for signal tower (EC001152)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Signal column element, connection module (ecI@ss13-27-37-12-32 [AKF050019])			
Connection type auxiliary circuit			Spring clamp connection
Suitable for tube mounting			No
Suitable for angle mounting			Yes
Suitable for floor mounting			Yes
Colour			Other
Suitable for AS interface			No
Suitable for M12 connector			No
Suitable for IO link			No