



Contactor, 24 V DC, 3 pole, 380 V 400 V, 5.5 kW, Contacts N/C = Normally closed= 1 NC, Screw terminals, DC operation

Part no. DILEM12-01-G(24VDC)  
127137  
EL Number 4110191  
(Norway)

General specifications		
Product name		Eaton Moeller® series DILEM Mini contactor
Part no.		DILEM12-01-G(24VDC)
EAN		4015081246724
Product Length/Depth		54 millimetre
Product height		58 millimetre
Product width		45 millimetre
Product weight		0.206 kilogram
Certifications		IEC/EN 60947-4-1 CE CSA VDE 0660 UL File No.: E29096 CSA File No.: 012528 UL 508 UL IEC/EN 60947 CSA Class No.: 3211-04 UL Category Control No.: NLDX CSA-C22.2 No. 14-05
Product Tradename		DILEM
Product Type		Mini contactor
Product Sub Type		None
Catalog Notes		Contacts according to EN 50012
Features & Functions		
Features		Positive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact module
Fitted with:		Auxiliary contact
General information		
Application		Mini Contactors for Motors and Resistive Loads Contactors for Motors
Degree of protection		IP20
Lifespan, mechanical		5,000,000 Operations 200,000 Operations (at 240 V, AC-15) 150,000 Operations (at 240 V, DC, L/R = 50 ms: 2 contacts in series 0.5 A)
Mounting position		As required (except vertical with terminals A1/A2 at the bottom)
Operating frequency		9000 mechanical Operations/h
Overvoltage category		III
Pollution degree		3
Product category		Contactors
Protection		Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
Rated impulse withstand voltage (Uimp)		6000 V AC
Shock resistance		10 g, N/O main contact, Basic unit without auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 10 g, N/C auxiliary contact, Basic unit without auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 20 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 20 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 10 g, N/O main contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
Utilization category		AC-4: Normal AC induction motors: starting, plugging, reversing, inching AC-3: Normal AC induction motors: starting, switch off during running AC-1: Non-inductive or slightly inductive loads, resistance furnaces
Voltage type		DC
Climatic environmental conditions		

Ambient operating temperature - min			-25 °C
Ambient operating temperature - max			50 °C
Ambient operating temperature (enclosed) - min			25 °C
Ambient operating temperature (enclosed) - max			40 °C
Ambient storage temperature - min			40 °C
Ambient storage temperature - max			80 °C
Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>Terminal capacities</b>			
Terminal capacity (flexible with ferrule)			1 x (0.75 - 1.5) mm <sup>2</sup> 2 x (0.75 - 1.5) mm <sup>2</sup>
Terminal capacity (solid)			2 x (0.75 - 2.5) mm <sup>2</sup> 1 x (0.75 - 2.5) mm <sup>2</sup>
Terminal capacity (solid/stranded AWG)			18 - 14
Stripping length (main cable)			8 mm
Screw size			M3.5, Terminal screw
Screwdriver size			0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver
Tightening torque			1.2 Nm, Screw terminals
<b>Electrical rating</b>			
Rated breaking capacity at 220/230 V			96 A
Rated breaking capacity at 380/400 V			96 A
Rated breaking capacity at 500 V			72 A
Rated operational power at AC-3, 240 V, 50 Hz			3 kW
Rated operational power at AC-3, 380/400 V, 50 Hz			5.5 kW
Rated operational power at AC-3, 415 V, 50 Hz			5.5 kW
Rated breaking capacity at 660/690 V			42 A
Rated making capacity up to 440 V (cos phi to IEC/EN 60947)			120 A
Rated operational power at AC-4, 220/230 V, 50 Hz			1.5 kW
Rated operational power at AC-4, 240 V, 50 Hz			1.5 kW
Rated operational power at AC-4, 415 V, 50 Hz			3 kW
Rated operational power at AC-4, 440 V, 50 Hz			3 kW
Rated operational power at AC-4, 500 V, 50 Hz			3 kW
Rated operational power at AC-4, 660/690 V, 50 Hz			3 kW
Rated operational voltage (Ue) at AC - max			690 V
Rated insulation voltage (Ui)			690 V
Rated operational current (Ie)			2.5 A at 24 V, DC L/R ≤ 15 ms (with 1 contact in series) 1.5 A at 100 V, DC L/R ≤ 15 ms (with 3 contacts in series) 0.5 A at 220 V, DC L/R ≤ 15 ms (with 3 contacts in series) 2.5 A at 60 V, DC L/R ≤ 15 ms (with 2 contacts in series)
Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V			22 A
Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V			6 A
Rated operational current (Ie) at AC-15, 380 V, 400 V, 415 V			3 A
Rated operational current (Ie) at AC-15, 500 V			1.5 A
Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V			12 A
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V			12 A
Rated operational current (Ie) at AC-3, 440 V			10.5 A
Rated operational current (Ie) at AC-3, 500 V			9 A
Rated operational current (Ie) at AC-3, 660 V, 690 V			5.2 A
Rated operational current (Ie) at AC-4, 220 V, 230 V, 240 V			6.6 A
Rated operational current (Ie) at AC-4, 440 V			6.6 A
Rated operational current (Ie) at AC-4, 500 V			5 A
Rated operational current (Ie) at AC-4, 660 V, 690 V			3.4 A
Rated operational current (Ie) at DC-1, 110 V			20 A
Rated operational current (Ie) at DC-1, 12 V			20 A
Rated operational current (Ie) at DC-1, 220 V			20 A
Rated operational current (Ie) at DC-1, 24 V			20 A
Rated operational current (Ie) at DC-1, 60 V			20 A

Safe isolation			300 V AC, Between coil and auxiliary contacts, According to EN 61140 300 V AC, Between auxiliary contacts, According to EN 61140 300 V AC, Between coil and contacts, According to EN 61140 300 V AC, Between the contacts, According to EN 61140
<b>Short-circuit rating</b>			
Short-circuit current rating (basic rating)			45 A, max. Fuse, SCCR (UL/CSA) 5 kA, SCCR (UL/CSA)
Short-circuit protection			6 A gG/gL, Max. Fuse 500V, Auxiliary contacts, Short-circuit rating without welding PKZM0-4, Maximum overcurrent protective device, Short-circuit protection only, Auxiliary contacts, Short-circuit rating without welding 10 A fast, Max. Fuse 500V, Auxiliary contacts, Short-circuit rating without welding
Short-circuit protection rating (type 1 coordination) at 500 V			35 A gG/gL
Short-circuit protection rating (type 2 coordination) at 500 V			20 A gG/gL
<b>Conventional thermal current Ith</b>			
Conventional thermal current Ith (1-pole, enclosed)			40 A
Conventional thermal current Ith (3-pole, enclosed)			16 A
Conventional thermal current Ith at 55°C (3-pole, open)			19 A
Conventional thermal current Ith of auxiliary contacts (1-pole, open)			10 A
Conventional thermal current Ith of main contacts (1-pole, open)			50 A
<b>Switching capacity</b>			
Switching capacity (main contacts, general use)			15 A, Maximum motor rating (UL/CSA)
Switching capacity (auxiliary contacts, general use)			10 A, 600 V AC, (UL/CSA) 0.5 A, 250 V DC, (UL/CSA)
Switching capacity (auxiliary contacts, pilot duty)			A600, AC operated (UL/CSA) P300, DC operated (UL/CSA)
<b>Magnet system</b>			
Arcing time			12 ms at 690 V AC
Changeover time			40 - 50 ms
Duty factor			100 %
Pick-up voltage			0.8 - 1.1 V DC x U <sub>c</sub>
Power consumption			2.3 VA/W at DC (Pick-up/Sealing power) Smoothed DC voltage or three-phase bridge rectifier
Rated control supply voltage (Us) at AC, 50 Hz - min			0 V
Rated control supply voltage (Us) at AC, 50 Hz - max			0 V
Rated control supply voltage (Us) at AC, 60 Hz - min			0 V
Rated control supply voltage (Us) at AC, 60 Hz - max			0 V
Rated control supply voltage (Us) at DC - min			24 V
Rated control supply voltage (Us) at DC - max			24 V
Switching time (AC operated, N/O, with auxiliary contact module, closing delay)			70 ms
Switching time (DC operated, make contacts, closing delay) - min			26 ms
Switching time (DC operated, make contacts, closing delay) - max			35 ms
Switching time (DC operated, make contacts, opening delay) - min			15 ms
Switching time (DC operated, make contacts, opening delay) - max			25 ms
<b>Motor rating</b>			
Assigned motor power at 115/120 V, 60 Hz, 1-phase			0.5 HP
Assigned motor power at 200/208 V, 60 Hz, 3-phase			2 HP
Assigned motor power at 230/240 V, 60 Hz, 1-phase			1.5 HP
Assigned motor power at 230/240 V, 60 Hz, 3-phase			3 HP
Assigned motor power at 460/480 V, 60 Hz, 3-phase			5 HP
Assigned motor power at 575/600 V, 60 Hz, 3-phase			5 HP
<b>Contacts</b>			
Control circuit reliability			< 2 λ, < 1 failure at 100,000,000 Operations (at U# = 24 V DC, Umin = 17 V, Imin = 5.4 mA)
Number of auxiliary contacts (normally closed contacts)			1
Number of auxiliary contacts (normally open contacts)			0
<b>Design verification</b>			
Equipment heat dissipation, current-dependent P <sub>vid</sub>			1.8 W
Heat dissipation capacity P <sub>diss</sub>			0 W

Heat dissipation per pole, current-dependent P <sub>vid</sub>		0.6 W
Rated operational current for specified heat dissipation (I <sub>n</sub> )		12 A
Static heat dissipation, non-current-dependent P <sub>vs</sub>		2.3 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss13-27-37-10-03 [AAB718020])			
Rated control supply voltage AC 50 Hz	V	0 - 0	
Rated control supply voltage AC 60 Hz	V	0 - 0	
Rated control supply voltage DC	V	24 - 24	
Voltage type for actuating		DC	
Number of normally closed contacts as main contact		0	
Number of normally open contacts as main contact		3	
Type of electrical connection of main circuit		Screw connection	
Operating voltage AC 50 Hz	V	24 - 690	
Operating voltage AC 60 Hz	V	24 - 690	
Rated operation current I <sub>e</sub> at AC-1, 400 V	A	22	
Rated operation current I <sub>e</sub> at AC-3, 400 V	A	12	
Rated operation power at AC-3, 400 V	kW	5.5	
Rated operation current I <sub>e</sub> at AC-4, 400 V	A	6.6	
Rated operation power at AC-4, 400 V	kW	3	
Rated operation power NEMA	kW	3.7	
Number of auxiliary contacts as normally open contact		0	
Number of auxiliary contacts as normally closed contact		1	
Modular version		No	
Width	mm	45	
Height	mm	58	
Depth	mm	54	