



Fuse-link, LV, 10 A, AC 690 V, 22 x 58 mm, gL/gG, IEC

EL Number
(Norway)

C22G10
1600218

Similar to illustration

General specifications		
Product name		Eaton Bussmann series low voltage cylindrical fuse
Part no.		C22G10
EAN		5027590495189
Product Length/Depth		58 millimetre
Product height		22.2 millimetre
Product width		22.2 millimetre
Product weight		53.9 gram
Compliances		GoST-R CE Marked RoHS Compliant
Certifications		IEC 60269
Product Tradename		None
Product Type		Low voltage cylindrical fuse
Product Sub Type		None
Electrical data		
Amperage Rating		10 A
Voltage rating		690 V
Voltage type		AC
Breaking capacity		80 kA
Utilization category		gG (cable protection/equipment protection)
Compatible fuse holder		
Suitable for		CH22 Modular fuse holder

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss13-27-14-20-02 [AFZ797018])		
Model		Ceramic fuse
Size		22x58 mm
Voltage type		AC
Rated current	A	10
Rated voltage	V	690
Utilization category		gG (cable protection/equipment protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	80
Power loss at rated current	W	1.5