



Fuse-link, LV, 40 A, AC 500 V, 14 x 51 mm, gL/gG, IEC

EL Number  
(Norway)

C14G40  
1600241

General specifications		
Product name		Eaton Bussmann series low voltage cylindrical fuse
Part no.		C14G40
EAN		5027590494076
Product Length/Depth		51 millimetre
Product height		14.3 millimetre
Product width		14.3 millimetre
Product weight		20.5 gram
Compliances		RoHS Compliant CE Marked GoST-R
Certifications		IEC 60269
Product Tradename		None
Product Type		Low voltage cylindrical fuse
Product Sub Type		None
Electrical data		
Amperage Rating		40 A
Voltage rating		500 V
Voltage type		AC
Breaking capacity		120 kA
Utilization category		gG (cable protection/equipment protection)
Compatible fuse holder		
Suitable for		CH14 Modular fuse holder

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss13-27-14-20-02 [AFZ797018])		
Model		Ceramic fuse
Size		14x51 mm
Voltage type		AC
Rated current	A	40
Rated voltage	V	500
Utilization category		gG (cable protection/equipment protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	120
Power loss at rated current	W	4.75