



Contactor, 3 pole, 380 V 400 V 18.5 kW, 24 V 50/60 Hz, AC operation, Screw terminals

Part no. DILM40(24V50/60HZ) 277770

General specifications		
Product name		Eaton Moeller® series DILM contactor
Part no.		DILM40(24V50/60HZ)
EAN		4015082777708
Product Length/Depth		132.1 millimetre
Product height		115 millimetre
Product width		55 millimetre
Product weight		0.872 kilogram
Certifications		CSA File No.: 012528 CSA-C22.2 No. 60947-4-1-14 UL Category Control No.: NLDX IEC/EN 60947-4-1 UL 60947-4-1 CSA CE CSA Class No.: 2411-03, 3211-04 UL File No.: E29096 UL IEC/EN 60947 VDE 0660
Product Tradename		DILM
Product Type		Contactor
Product Sub Type		None
Catalog Notes		Contacts according to EN 50012
General information		
Application		Contactors for Motors
Connection		Screw terminals
Degree of protection		IP00
Frame size		FS3
Lifespan, mechanical		10,000,000 Operations (AC operated) 7,000,000 Operations (Coil 50/60 Hz)
Operating frequency		5000 mechanical Operations/h (AC operated)
Overvoltage category		III
Pollution degree		3
Product category		Contactors
Protection		Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
Rated impulse withstand voltage (Uimp)		8000 V AC
Resistance per pole		1.9 mΩ
Suitable for		Also motors with efficiency class IE3
Utilization category		AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-4: Normal AC induction motors: starting, plugging, reversing, inching AC-3: Normal AC induction motors: starting, switch off during running
Voltage type		AC
Ambient conditions, mechanical		
Shock resistance		10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms 5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms 5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
Climatic environmental conditions		

Altitude		Max. 2000 m
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		60 °C
Ambient operating temperature (enclosed) - min		25 °C
Ambient operating temperature (enclosed) - max		40 °C
Ambient storage temperature - min		40 °C
Ambient storage temperature - max		80 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>Electro magnetic compatibility</b>		
Emitted interference		According to EN 60947-1
Interference immunity		According to EN 60947-1
<b>Terminal capacities</b>		
Terminal capacity (copper band)		2 x (6 x 9 x 0.8) mm (Number of segments x width x thickness), Main cables
Terminal capacity (flexible with ferrule)		2 x (0.75 - 25) mm <sup>2</sup> , Main cables 1 x (0.75 - 35) mm <sup>2</sup> , Main cables 2 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables 1 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables
Terminal capacity (solid)		2 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables 1 x (0.75 - 4) mm <sup>2</sup> , Control circuit cables 1 x (0.75 - 16) mm <sup>2</sup> , Main cables 2 x (0.75 - 16) mm <sup>2</sup> , Main cables
Terminal capacity (solid/stranded AWG)		18 - 14, Control circuit cables Single 14 - 1, double 14 - 2, Main cables
Terminal capacity (stranded)		1 x (16 - 50) mm <sup>2</sup> , Main cables 2 x (16 - 35) mm <sup>2</sup> , Main cables
Stripping length (main cable)		14 mm
Stripping length (control circuit cable)		10 mm
Screw size		M6, Terminal screw, Main cables M3.5, Terminal screw, Control circuit cables
Screwdriver size		0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver
Tightening torque		1.2 Nm, Screw terminals, Control circuit cables 3.3 Nm, Screw terminals, Main cables
<b>Electrical rating</b>		
Rated breaking capacity at 220/230 V		400 A
Rated breaking capacity at 380/400 V		400 A
Rated breaking capacity at 500 V		400 A
Rated breaking capacity at 660/690 V		250 A
Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V		60 A
Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V		40 A
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V		40 A
Rated operational current (Ie) at AC-3, 440 V		40 A
Rated operational current (Ie) at AC-3, 500 V		40 A
Rated operational current (Ie) at AC-3, 660 V, 690 V		25 A
Rated operational current (Ie) at AC-4, 220 V, 230 V, 240 V		18 A
Rated operational current (Ie) at AC-4, 440 V		18 A
Rated operational current (Ie) at AC-4, 500 V		18 A
Rated operational current (Ie) at AC-4, 660 V, 690 V		14 A
Rated operational current (Ie) at DC-1, 60 V		50 A
Rated operational current (Ie) at DC-1, 110 V		50 A
Rated operational current (Ie) at DC-1, 220 V		45 A
Rated insulation voltage (Ui)		690 V
Rated making capacity up to 690 V (cos phi to IEC/EN 60947)		560 A
Rated operational power at AC-3, 240 V, 50 Hz		13.5 kW
Rated operational power at AC-3, 380/400 V, 50 Hz		18.5 kW
Rated operational power at AC-3, 415 V, 50 Hz		24 kW
Rated operational power at AC-3, 440 V, 50 Hz		25 kW
Rated operational power at AC-3, 500 V, 50 Hz		28 kW
Rated operational power at AC-3, 690 V, 50 Hz		23 kW

Rated operational power at AC-4, 220/230 V, 50 Hz		5 kW
Rated operational power at AC-4, 240 V, 50 Hz		5.5 kW
Rated operational power at AC-4, 415 V, 50 Hz		9.5 kW
Rated operational power at AC-4, 440 V, 50 Hz		10 kW
Rated operational power at AC-4, 500 V, 50 Hz		11 kW
Rated operational power at AC-4, 660/690 V, 50 Hz		12 kW
Rated operational voltage (Ue) at AC - max		690 V
<b>Short-circuit rating</b>		
Short-circuit current rating (basic rating)		10 kA, SCCR (UL/CSA) 250 A, max. Fuse, SCCR (UL/CSA) 250 A, max. CB, SCCR (UL/CSA)
Short-circuit current rating (high fault at 480 V)		250/150 A, Class J, max. Fuse, SCCR (UL/CSA) 30/100 kA, Fuse, SCCR (UL/CSA) 100 A, max. CB, SCCR (UL/CSA) 65 kA, CB, SCCR (UL/CSA)
Short-circuit current rating (high fault at 600 V)		250 A, max. CB, SCCR (UL/CSA) 250/150 A, Class J, max. Fuse, SCCR (UL/CSA) 30 kA, CB, SCCR (UL/CSA) 30/100 kA, Fuse, SCCR (UL/CSA)
Short-circuit protection rating (type 1 coordination) at 400 V		125 A gG/gL
Short-circuit protection rating (type 1 coordination) at 690 V		80 A gG/gL
Short-circuit protection rating (type 2 coordination) at 400 V		63 A gG/gL
Short-circuit protection rating (type 2 coordination) at 690 V		50 A gG/gL
<b>Conventional thermal current Ith</b>		
Conventional thermal current Ith (1-pole, enclosed)		112 A
Conventional thermal current Ith (3-pole, enclosed)		45 A
Conventional thermal current Ith at 55°C (3-pole, open)		55 A
Conventional thermal current Ith at 60°C (3-pole, open)		50 A
Conventional thermal current Ith of main contacts (1-pole, open)		125 A
<b>Switching capacity</b>		
Switching capacity (main contacts, general use)		63 A, Maximum motor rating (UL/CSA)
<b>Magnet system</b>		
Arcing time		10 ms
Drop-out voltage		AC operated: 0.6 - 0.3 x UC, AC operated
Duty factor		100 %
Pick-up voltage		0.8 - 1.1 V AC x Uc
Power consumption, pick-up, 50 Hz		168 VA, Dual-frequency coil in a cold state and 1.0 x Us 154 VA, Dual-frequency coil in a cold state and 1.0 x Us
Power consumption, pick-up, 60 Hz		154 VA, Dual-frequency coil in a cold state and 1.0 x Us 168 VA, Dual-frequency coil in a cold state and 1.0 x Us
Power consumption, sealing, 50 Hz		4.1 W, Dual-frequency coil in a cold state and 1.0 x Us
Power consumption, sealing, 60 Hz		4.1 W, Dual-frequency coil in a cold state and 1.0 x Us 14 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz 22 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz
Rated control supply voltage (Us) at AC, 50 Hz - min		24 V
Rated control supply voltage (Us) at AC, 50 Hz - max		24 V
Rated control supply voltage (Us) at AC, 60 Hz - min		24 V
Rated control supply voltage (Us) at AC, 60 Hz - max		24 V
Rated control supply voltage (Us) at DC - min		0 V
Rated control supply voltage (Us) at DC - max		0 V
Switching time (AC operated, make contacts, closing delay) - min		12 ms
Switching time (AC operated, make contacts, closing delay) - max		18 ms
Switching time (AC operated, make contacts, opening delay) - min		8 ms
Switching time (AC operated, make contacts, opening delay) - max		13 ms
<b>Motor rating</b>		
Assigned motor power at 115/120 V, 60 Hz, 1-phase		3 HP
Assigned motor power at 200/208 V, 60 Hz, 3-phase		10 HP
Assigned motor power at 230/240 V, 60 Hz, 1-phase		7.5 HP
Assigned motor power at 230/240 V, 60 Hz, 3-phase		15 HP

Assigned motor power at 460/480 V, 60 Hz, 3-phase			30 HP
Assigned motor power at 575/600 V, 60 Hz, 3-phase			40 HP
Communication			
Connection to SmartWire-DT			No
Contacts			
Number of auxiliary contacts (normally closed contacts)			0
Number of auxiliary contacts (normally open contacts)			0
Number of contacts (normally closed) as main contact			0
Safety			
Safe isolation			440 V AC, Between coil and contacts, According to EN 61140 440 V AC, Between the contacts, According to EN 61140
Special purpose ratings			
Special purpose rating of ballast electrical discharge lamps			79 A (600V 60Hz 3phase, 347V 60Hz 1phase) 79 A (480V 60Hz 3phase, 277V 60Hz 1phase)
Special purpose rating of elevator control			32 A, 600 V 60 Hz 3-ph, (UL/CSA) 30 HP, 600 V 60 Hz 3-ph, (UL/CSA) 25 HP, 480 V 60 Hz 3-ph, (UL/CSA) 28 A, 240 V 60 Hz 3-ph, (UL/CSA) 34 A, 480 V 60 Hz 3-ph, (UL/CSA) 25.3 A, 200 V 60 Hz 3-ph, (UL/CSA) 7.5 HP, 200 V 60 Hz 3-ph, (UL/CSA) 10 HP, 240 V 60 Hz 3-ph, (UL/CSA)
Special purpose rating of resistance air heating			79 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA) 79 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)
Special purpose rating of tungsten incandescent lamps			74 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA) 74 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)
Design verification			
Equipment heat dissipation, current-dependent Pvid			6.6 W
Heat dissipation capacity Pdis			0 W
Heat dissipation per pole, current-dependent Pvid			2.2 W
Rated operational current for specified heat dissipation (In)			40 A
Static heat dissipation, non-current-dependent Pvs			4.1 W
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecI@ss13-27-37-10-03 [AAB718020])

Rated control supply voltage AC 50 Hz	V	24 - 24
Rated control supply voltage AC 60 Hz	V	24 - 24
Rated control supply voltage DC	V	0 - 0
Voltage type for actuating		AC
Number of normally closed contacts as main contact		0
Number of normally open contacts as main contact		3
Type of electrical connection of main circuit		Screw connection
Operating voltage AC 50 Hz	V	230 - 690
Operating voltage AC 60 Hz	V	230 - 690
Rated operation current I <sub>e</sub> at AC-1, 400 V	A	60
Rated operation current I <sub>e</sub> at AC-3, 400 V	A	40
Rated operation power at AC-3, 400 V	kW	18.5
Rated operation current I <sub>e</sub> at AC-4, 400 V	A	18
Rated operation power at AC-4, 400 V	kW	9
Rated operation power NEMA	kW	22
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as normally closed contact		0
Modular version		No
Width	mm	55
Height	mm	115
Depth	mm	132.1