



Tunnel terminal, 3p, 1 page, max. 185mm², size 3

Part no. NZM3-XKA1
271459
EL Number 4358873
(Norway)

General specifications		
Product name		Eaton Moeller series NZM connection type
Part no.		NZM3-XKA1
EAN		4015082714598
Product Length/Depth		92.5 millimetre
Product height		102 millimetre
Product width		137 millimetre
Product weight		0.691 kilogram
Compliances		RoHS conform IEC
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Connection type
Delivery program		
Type		Tunnel terminal Accessory
Number of poles		Three-pole
Amperage Rating		≤ 350 A
Frame		NZM3
Suitable for		Copper cable Three-pole
Used with		NZM3, PN3, N(S)3
Technical Data - Mechanical - Terminals		
Terminal capacity (stranded cable)		6 - 350 AWG/kcmil (1x) 16 mm ² - 185 mm ² (1x) at digital input of supply connection
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Additional information		
Model		Other

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Wiring set for power circuit breaker (EC002050)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Wiring set for circuit breaker (ecl@ss13-27-37-04-24 [ACN957016])		
Suitable for number of poles		3
Model		Other