



Timing relay, 1W, 0.05s-100h, multi-function, 24-240VAC/DC

Part no. ETR4-69-A
031891
EL Number 4133309
(Norway)

General specifications		
Product name		Eaton Moeller® series ETR4 Timing relay
Part no.		ETR4-69-A
EAN		4015080318910
Product Length/Depth		103 millimetre
Product height		83 millimetre
Product width		23 millimetre
Product weight		0.11 kilogram
Certifications		IEC/EN 61000-4-2 UL 508 VDE 0435 CSA UL CE UL Category Control No.: NKCR CSA File No.: 012528 IEC/EN 60947-5-1 IEC/EN 61000-4-3 Standard IEC/EN 61812 UL File No.: E29184 CSA-22.2 No. 14 CSA Class No.: 3211-03 IEC/EN 61812-1
Product Tradename		ETR4
Product Type		Timing relay
Product Sub Type		None
Features & Functions		
Electric connection type		Screw connection
Functions		Pulse shaping Flashing, starting with pause, fixed time Fleeting contact on de-energization Flashing, starting with pulse, fixed time Delay-on energization On-delayed Clock function, starting with pulse, variable Clock function, starting with pause, variable Fleeting contact on energization Multi-functional Delay on de-energization Pulse forming Off-delayed Outputs, reversible delayed/undelayed Adjustable timing function Pulse generating On- and Off-delayed Flashing, pulse initiating
General information		
Degree of protection		Terminals: IP20 IP20
Lifespan, mechanical		30,000,000 Operations (AC operated) 30,000,000 Operations (DC operated)
Mounting position		As required
Number of contacts (change-over contacts)		1
Overvoltage category		III
Pollution degree		2
Product category		ETR4 timing relays
Rated impulse withstand voltage (Uimp)		6000 V AC 4000 V AC
Shock resistance		4 g, Make contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms
Suitable for		DIN rail (top hat rail) mounting
Terminal capacity		2 x (0.5 - 1.5) mm², solid 1 x (0.5 - 2.5) mm², solid

			2 x (0.5 - 1.5) mm ² , flexible with ferrule 1 x (20 - 14) AWG, solid or stranded 1 x (0.5 - 2.5) mm ² , flexible with ferrule
Time range - min			0.05 s
Time range - max			360000 s
Type			Timer relay
Voltage type			AC/DC
Climatic environmental conditions			
Ambient operating temperature - min			-25 °C
Ambient operating temperature - max			60 °C
Ambient operating temperature (enclosed) - min			-25 °C
Ambient operating temperature (enclosed) - max			45 °C
Ambient storage temperature - min			-45 °C
Ambient storage temperature - max			85 °C
Climatic proofing			Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Electro magnetic compatibility			
Air discharge			8 kV
Burst impulse			1 kV, Signal cable According to IEC/EN 61000-4-4 2 kV, Supply cable
Contact discharge			6 kV
Electromagnetic fields			1 V/m at 2.0 - 2.7 GHz (according to IEC EN 61000-4-3) 10 V/m at 80 - 1000 MHz (according to IEC EN 61000-4-3) 3 V/m at 1.4 - 2 GHz (according to IEC EN 61000-4-3)
Immunity to line-conducted interference			10 V (according to IEC/EN 61000-4-6)
Radio interference class			Class B (EN 55011, conducted) Class B (EN 55011, radiated)
Surge rating			According to IEC/EN 61000-4-5, power pulses (Surge), EMC 4 kV, asymmetrical, power pulses (Surge), EMC 2 kV, symmetrical, power pulses (Surge), EMC
Electrical rating			
Conventional thermal current I _{th} of auxiliary contacts (1-pole, open)			6 A
Mains voltage tolerance			24 - 240 V AC (at 50/60 Hz) 24 – 240 V DC
Nominal current			3 A
Rated breaking capacity			1.1 x I _# (DC-11 L/R - 40 ms) 3 A at AC-14 (cos φ = 0.3 440 V) 3 A at AC-15 (cos φ = 0.3 220 V)
Rated making capacity			50 A (AC-15 cos φ = 0.3 220 V) 48 A (AC-14 cos φ = 0.3 400 V) 1.1 x I _# (DC-11 L/R - 40 ms)
Rated operational current (I _e)			3 A at AC-14, 300 V (NC) 3 A at AC-14, 440 V 1.2 A at DC-11, L/R max. 50 ms 3 A at AC-15, 220 V 230 V 240 V 3 A at AC-15, 300 V 3 A at AC-15, 380 V 400 V 415 V 1.5 A at DC-11, 24 V 3 A at AC-14, 380 V 400 V 415 V
Rated operational voltage (U _e) at AC - max			440 V
Safe isolation			250 V AC, Between coil and auxiliary contacts, According to EN 61140 250 V AC, Between auxiliary contacts, According to EN 61140
Short-circuit protection rating			Max. 6 A gG/gL, Fuse, Short-circuit rating without welding, Contacts Max. 6 A gG/gL, fuse, Without welding, Contacts
Magnet system			
Command time			50 ms, AC 30 ms, DC
Contact changeover time			4 ms
Duty factor			100 %
Operating frequency			4000 Operations/h
Pick-up voltage			0.85 - 1.1 V AC x U _c 0.7 - 1.1 V DC x U _c
Power consumption			1.8 W at DC (Sealing power) 2 VA at AC (Sealing power) 1.8 W at DC (Pick-up power) 2 VA at AC (Pick-up power)

Rated control supply voltage (Us) at AC, 50 Hz - min		24 V
Rated control supply voltage (Us) at AC, 50 Hz - max		240 V
Rated control supply voltage (Us) at AC, 60 Hz - min		24 V
Rated control supply voltage (Us) at AC, 60 Hz - max		240 V
Rated control supply voltage (Us) at DC - min		24 V
Rated control supply voltage (Us) at DC - max		240 V
Recovery time		70 ms (after 100 % time delay)
Repetition accuracy		≤ 0.5 % (deviation)
Design verification		
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		1.4 W
Rated operational current for specified heat dissipation (In)		6 A
Static heat dissipation, non-current-dependent Pvs		1.8 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Relays (EG000019) / Timer relay (EC001439)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Relay and socket / Timer relay (ecI@ss13-27-37-16-05 [AKF092018])		
Type of electric connection		Screw connection
Complete with socket		No
Suitable for DIN rail (top hat rail) mounting		Yes
Suitable for front mounting		No
Pluggable on auxiliary contact block		No
Function delay-on energization		Yes
Function delay on de-energization		Yes
Function floating contact on energization		Yes
Function floating contact on de-energization		Yes
Function star-delta		No
Function pulse shaping		Yes
Function flashing, starting with pause, fixed time		Yes
Function flashing, starting with pulse, fixed time		Yes
Clock function, starting with pause, variable		Yes

Clock function, starting with pulse, variable		Yes
Time range	s	0.05 - 360000
Remote operation possible		No
Suitable as remote control		No
Rated control supply voltage AC 50 Hz	V	24 - 240
Rated control supply voltage AC 60 Hz	V	24 - 240
Rated control supply voltage DC	V	24 - 240
Voltage type for actuating		AC/DC
Number of outputs, undelayed, normally closed contact		0
Number of outputs, undelayed, normally open contact		0
Number of outputs, undelayed, change-over contact		0
Number of outputs, delayed, normally closed contact		0
Number of outputs, delayed, normally open contact		0
Number of outputs, delayed, change-over contact		0
Outputs, reversible delayed/undelayed		Yes
With semiconductor output		No
Material of contact insert		
Material contact		
Material of contact surface		
Operating voltage AC 50 Hz	V	24 - 240
Operating voltage AC 60 Hz	V	24 - 240
Operating voltage DC	V	24 - 240
Voltage type (operating voltage)		AC/DC
Nominal current	A	3
Max. starting current	A	
Degree of protection (IP)		IP20
Relay technology category according to IEC 61810-7		
Width	mm	23
Height	mm	83
Depth	mm	103