# Eaton 276258

### Catalog Number: 276258

Main load disconnector Switch with isolation function, highly wear resistant contacts and classified for the use in rail rolling stock, 240 V, 20 A, 1P

#### General specifications



Eaton Moeller series IS Disconnector

EAN

276258

Product Length/Depth

Catalog Number

4015082762582

60 mm

**Product Height** 

**Product Width** 

80 mm

17.7 mm

**Product Weight** 

Compliances

0.1 kg

RoHS conform

Certifications

Model Code

EN45545-2

IS-20/1

IEC 61373



## Product specifications Type IS. Main load disconnector switch Application Switchgear for industrial and advanced commercial applications Degree of protection IP40 IP10 **Terminals** Lift terminal Equipment heat dissipation, current-dependent 0.4 W Imprint/indication Symbol "arrows" Lamp socket Other Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Built-in depth 69.5 mm Heat dissipation capacity Heat dissipation per pole, current-dependent 0.6 W Lamp power 0 W Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts)

Amperage rating

Color calotte

20 A

Other

#### Resources

Declarations of conformity

DA-DC-03\_IS

**Drawings** 

eaton-dimensions-mas-is.jpg

eCAD model

ETN.IS-20\_1.edz

mCAD model

DA-CD-is\_1p

DA-CS-is\_1p

Wiring diagrams

IS\_1P

| Switch type Other Off switch Rated short-time withstand current (Icw) 1 kA Voltage type AC Lamp type Other Number of contacts (normally open contacts) 1 Rated operational current for specified heat dissipation (In) 20 A Rated operational voltage (Ue) - max 240 V Rated switching capacity 12.5 kA Static heat dissipation, non-current-dependent 0 W Voltage rating - min 240 V Width in number of modular spacings 1 Number of poles Single-pole |       |
|---|-------|
| 1 kA  Voltage type  AC  Lamp type Other  Number of contacts (normally open contacts)  1  Rated operational current for specified heat dissipation (In) 20 A  Rated operational voltage (Ue) - max 240 V  Rated switching capacity 12.5 kA  Static heat dissipation, non-current-dependent 0 W  Voltage rating - min 240 V  Width in number of modular spacings 1  Number of poles   | Other |
| AC  Lamp type Other  Number of contacts (normally open contacts)  1  Rated operational current for specified heat dissipation (In) 20 A  Rated operational voltage (Ue) - max 240 V  Rated switching capacity 12.5 kA  Static heat dissipation, non-current-dependent 0 W  Voltage rating - min 240 V  Width in number of modular spacings 1  Number of poles   |       |
| Other  Number of contacts (normally open contacts)  1  Rated operational current for specified heat dissipation (In) 20 A  Rated operational voltage (Ue) - max 240 V  Rated switching capacity 12.5 kA  Static heat dissipation, non-current-dependent 0 W  Voltage rating - min 240 V  Width in number of modular spacings 1  Number of poles   |       |
| Rated operational current for specified heat dissipation (In) 20 A  Rated operational voltage (Ue) - max 240 V  Rated switching capacity 12.5 kA  Static heat dissipation, non-current-dependent 0 W  Voltage rating - min 240 V  Width in number of modular spacings 1  Number of poles  |       |
| 20 A  Rated operational voltage (Ue) - max 240 V  Rated switching capacity 12.5 kA  Static heat dissipation, non-current-dependent 0 W  Voltage rating - min 240 V  Width in number of modular spacings 1  Number of poles  |       |
| 240 V  Rated switching capacity  12.5 kA  Static heat dissipation, non-current-dependent  0 W  Voltage rating - min  240 V  Width in number of modular spacings  1  Number of poles   |       |
| 12.5 kA  Static heat dissipation, non-current-dependent 0 W  Voltage rating - min 240 V  Width in number of modular spacings 1  Number of poles   |       |
| 0 W  Voltage rating - min 240 V  Width in number of modular spacings 1  Number of poles   |       |
| 240 V  Width in number of modular spacings  1  Number of poles  |       |
| 1 Number of poles   |       |
|   |       |
|   |       |



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia