Eaton 276273

Catalog Number: 276273

Main load disconnector Switch with isolation function, highly wear resistant contacts and classified for the use in rail rolling stock, 240/415 V, 40 A, 4P

General specifications



4015082762735

Product Height 80 mm

EAN

Product Weight

0.406 kg

Certifications EN45545-2 IEC 61373 Catalog Number

276273

Product Length/Depth

60 mm

Product Width

70.8 mm

Compliances

RoHS conform

Model Code

IS-40/4





Product specifications Type IS. Main load disconnector switch Application Switchgear for industrial and advanced commercial applications Degree of protection IP40 IP10 **Terminals** Lift terminal Equipment heat dissipation, current-dependent 2.8 W Imprint/indication Symbol "arrows" Lamp socket Other Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Built-in depth 69.5 mm Heat dissipation capacity Heat dissipation per pole, current-dependent 1.9 W Lamp power 0 W Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts)

Amperage rating

Color calotte

40 A

Other

Resources

Declarations of conformity

DA-DC-03_IS

Drawings

eaton-dimensions-mas-is.jpg

122I173

eCAD model

ETN.IS-40_4.edz

mCAD model

DA-CD-is_4p

DA-CS-is_4p

Wiring diagrams

IS_4P

Switch type Other
Rated short-time withstand current (lcw) 1 kA
Voltage type AC
Lamp type Other
Number of contacts (normally open contacts) 4
Rated operational current for specified heat dissipation (In) 40 A
Rated operational voltage (Ue) - max 415 V
Rated switching capacity 12.5 kA
Static heat dissipation, non-current-dependent 0 W
Voltage rating - min 240 V
Width in number of modular spacings 4
Number of poles Four-pole



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All rights

reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia