Eaton 276282



Catalog Number: 276282

Main load disconnector Switch with isolation function, highly wear resistant contacts and classified for the use in rail rolling stock, 240 V, 100 A, 1P

General Specifications

Product Name Catalog Number

Eaton Moeller series IS Disconnector 276282

Product Length/Depth Product Height

60 mm 80 mm

Product Width Product Weight

17.7 mm 0.101 kg

Compliances Certifications

RoHS conform EN45545-2

IEC 61373

EAN Model Code

4015082762827 IS-100/1



Product specifications Type IS. Main load disconnector switch Application Switchgear for industrial and advanced commercial applications Degree of protection IP40 IP10 **Terminals** Lift terminal Equipment heat dissipation, current-dependent 3.9 W Imprint/indication Symbol "arrows" Lamp socket Other Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Built-in depth 69.5 mm Heat dissipation capacity Heat dissipation per pole, current-dependent 3.9 W Lamp power 0 W Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts)

Amperage rating

Color calotte

100 A

Other

Resources

Declarations of conformity

DA-DC-03_IS

Drawings

eaton-dimensions-mas-is.jpg

122I155

eCAD model

ETN.IS-100_1.edz

mCAD model

DA-CD-is_1p

DA-CS-is_1p

Wiring diagrams

IS_1P

Switch type Other Off switch
Rated short-time withstand current (Icw) 2 kA
Voltage type AC
Lamp type Other
Number of contacts (normally open contacts) 1
Rated operational current for specified heat dissipation (In) 100 A
Rated operational voltage (Ue) - max 240 V
Rated switching capacity 10 kA
Static heat dissipation, non-current-dependent 0 W
Voltage rating - min 240 V
Width in number of modular spacings 1
Number of poles Single-pole



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia