

THEOS MINI SR/T1



Part number	06222996
Lampholder:	LED
Light Source:	LED
Wattage:	70 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	II
Degree of protection:	IP66
IK-J-xxIP:	IK08 9J xx5
CRI:	70
Kelvin:	4000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	ROAD REFLECTOR
Lightsource lumen output:	8608 lm
Luminaire lumen output:	6944 lm
L:	L80
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-40°
Ta MAX luminaire:	45°



Description

Photometric data

Technical drawings

- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating

- High-transparency polycarbonate lenses for best light transmission

- Optics for narrow roads


- Switch splitter automatically disconnects the power supply when the cable cover is opened

- High efficiency electronic driver

- Compliant with the UNI 10819 Standard and with the Italian regional laws on light pollution


- The “SECURE LIGHT DISTRIBUTION” system guarantees uniform light distribution even in the remote case of LED failures

- 3000 K and 5000 K available upon request



OPTIONAL ACCESSORIES

THEOS



14174796
Wall mount bracket THEOS



14077796
Hot-dipped galvanized wall angled
steel bracket, cataphoresis and
polyester powder